PALLET HANDLING EQUIPMENT

HEAVY-DUTY SERIES

Rugged construction makes these pallet trucks the best value for your material handling needs. Forks feature entry rollers and tapered design for easy pallet entry and are reinforced for heavy-duty loads. The 3-function hand control (raise, neutral and lower) and the spring-loaded self-righting safety loop handle enhance comfort and ease of operation. Hardened chrome piston with protective dust cover for dependable performance. Durable powder coat finish.

HYDRAULIC PALLET TRUCKS

- Heavy-duty polyurethane tread bonded to cast iron core steering wheels and rollers provide superior performance
- 6 1/4" (158.75 mm) wide forks
- High visibility orange
- · 2-year limited warranty



KILETON

Model	Fo	rks	Frame	Fork	Capacity
No.	Lowered"	Raised"	Width"	Length"	lbs.
MJ484	2 7/8	7 3/4	20 1/2	36	5500
MJ485	2 7/8	7 3/4	20 1/2	42	5500
MJ486	2 7/8	7 3/4	20 1/2	48	5500
MJ487	2 7/8	7 3/4	27	36	5500
MJ488	2 7/8	7 3/4	27	42	5500
MJ489	2 7/8	7 3/4	27	48	5500
ML372*	2 7/8	7 3/4	27	48	5500

* Heavy-duty nylon wheels

HYDRAULIC PALLET TRUCKS

- Heavy-duty polyurethane tread bonded to cast iron core steering wheels and rollers provide superior performance
- Double rollers for easy moving of extra heavy loads
- Reinforced fork channels deliver exceptional durability
- 6 1/4" (158.75 mm) wide forks
- Kleton blue
- · 2-year limited warranty





* Heavy-duty nylon wheels

STANDARD-DUTY HYDRAULIC PALLET TRUCKS

- Heavy-duty polyurethane tread bonded to cast iron core steering wheels and rollers provide superior performance
- Heavy-duty plastic rollers facilitate entry and exit of pallets
- 6 1/4" (158.75 mm) wide forks
- High visibility yellow
- 1-year limited warranty



KLETON

Model	Forks		Frame	Fork	Capacity
No.	Lowered"	Raised"	Width"	Length"	lbs.
ML966	3 1/4	7 3/4	20 1/2	36	5500
ML967	3 1/4	7 3/4	20 1/2	42	5500
ML968	3 1/4	7 3/4	20 1/2	48	5500
ML969	3 1/4	7 3/4	27	36	5500
ML970	3 1/4	7 3/4	27	42	5500
ML971	3 1/4	7 3/4	27	48	5500
ML972*	3 1/4	7 3/4	27	48	5500

* All nylon core steering wheels and rollers

SUPER HEAVY-DUTY HYDRAULIC PALLET TRUCK

- Extra heavy-duty all steel steering wheels and rollers provide maximum mobility and performance
- Double rollers for easy moving of extra heavy loads
- Heavy-duty plastic exit rollers facilitate entry and exit of pallets
- 6 1/4" (158.75 mm) wide forks
- Dark blue
- 2-year limited warranty



Forks feature double

entry rollers and

tapered design for easy

pallet entry



Model	Foi	rks	Frame	Fork	Capacity
No.	Lowered"	Raised"	Width"	Length"	lbs.
ML994	3	7 3/8	27	48	11 000

6' LONG FORK HYDRAULIC PALLET TRUCKS

- Heavy-duty polyurethane thread bonded to cast iron core steering wheels and rollers provide superior performance
- Nylon exit roller facilitates entry and exit of pallets
- 6 1/4" (158.75 mm) wide forks
- · Lowered pallet truck height: 3"
- Raised pallet truck height: 7 5/8"
 Capacity: Up to 5500 lbs
- Capacity: Up to 5500 lbs.
- High visibility yellow
- 2-year limited warranty



Model	Fork	Fork
No.	Width"	Length"
MN459	27	72



LOW PROFILE HYDRAULIC PALLET TRUCKS

- Permits the handling of pallets and containers that are lower than the standard height
- Heavy-duty polyurethane tread bonded to cast iron core steering wheels and all steel rollers provide superior performance
- 1.5" exit ramp facilitates exit of pallets
- 6" (152 mm) wide forks
- Lowered pallet truck height: 2"
- Raised pallet truck height: 5 1/2"
- High visibility orange
- · 2-year limited warranty







PALLET HANDLING EQUIPMENT

MULTI-DIRECTIONAL HYDRAULIC PALLET TRUCKS

- Transrollers permit lateral movement in addition to forward/backward
- Heavy-duty polyurethane tread bonded to cast iron core steering wheels provide superior performance
- Double load rollers, one polyurethane tread bonded to cast iron core and one nylon for easy moving of extra heavy loads
- 2 1/5" exit ramp facilitates exit of pallets
- 6 1/4" (158.75 mm) wide forks
- · Lowered pallet truck height: 3"
- Raised pallet truck height: 7 1/2"
- Capacity: Up to 5500 lbs. in standard mode and up to 3300 lbs. in lateral mode
- · High visibility orange
- · 2-year limited warranty



Model	Frame	Fork
No.	Width"	Length"
MN062	27	48



GALVANIZED HYDRAULIC PALLET TRUCKS

- Heavy-duty all nylon steering wheels and rollers provide superior mobility and performance
- Nylon exit roller facilitates entry and exit of pallets
- 6 1/4" (158.75 mm) wide forks
- Lowered pallet truck height: 3"
- Raised pallet truck height: 7 1/16"
- Galvanized finish offers corrosion resistance and is ideal for wet and cold conditions
- 2-year limited warranty



KILETON

Model No.	Frame Width"	Fork Length"	Capacity lbs.
MN059	27	48	5500
MN648	27	42	5500

4-WAY HYDRAULIC PALLET TRUCKS

- · Can enter pallet from all four sides
- Reinforced forks
- Adjustable fork connecting rods
- · Steel 1.70" load wheels
- 6" polyurethane steering wheels
- · 3-year limited warranty





Model No.	Frame Width"	Fork Length"	Capacity lbs.
MN136	33	48	4000

DIGITAL SCALE HYDRAULIC PALLET TRUCKS

- · Permits the weighing of skids and containers while handling them
- Mettler Toledo digital cUL listed scale offers maximum precision on load weights
- Heavy-duty polyurethane tread bonded to cast iron core steering wheels and rollers provide superior performance
- Nylon roller facilitates entry and exit of pallets
- 65/8" (168 mm) wide forks
- Lowered pallet truck height: 3"
- Raised pallet truck height: 7 11/16"
- · High visibility orange
- · 2-year limited warranty





Model	Frame	Fork	Capacity
No.	Width"	Length"	lbs.
MN063	27	44 1/2	4400

STAINLESS STEEL HYDRAULIC PALLET TRUCKS

- Heavy-duty all nylon steering wheels and rollers provide superior mobility and performance
- · Nylon exit roller facilitates entry and exit of pallets
- 6 1/4" (158.75 mm) wide forks
- High grade 304 stainless steel is ideal for medical, food, sanitary, pharmaceutical, wet and cold applications
- · 2-year limited warranty




KILETON

Model	el Fork Height		Fork Height Fran		Frame	Fork	Capacity
No.	Lowered"	Raised"	Width"	Length"	lbs.		
MN060	3	7 1/16	27	48	5500		

ECO I-55 AUTOMOTIVE BRAKE PALLET TRUCK

- Quality german-designed pump
- 200 degree handle pivot
- · Ergonomic cushioned handle
- 3-postion finger tip control
- High-quality powder coat finish
- Polyurethane wheels and load rollers
- Fork width: 6.3"
- Raised height: 7.9"
- Lowered height: 2.9"






PALLET HANDLING EQUIPMENT

ADJUSTABLE WIDTH PALLET TRUCKS

- Overall fork width adjusts from 21" to 27"
- Fork length: 48"
- 7" mold-on polyurethane steering wheel
- 3" mold-on polyurethane load wheels
- 6" (152 mm) wide forks
- · Raised height: 7 3/4"
- Lowered height: 3"Capacity: 5500 lbs.
- 5-year limited warranty

Model No. MI820





WESCO*

ALL TERRAIN PALLET TRUCKS

- Welded steel tubular frame construction for maximum strength
- Features large pneumatic wheels for use on gravel, dirt and other types of rough tterrain
- · Wheels include sealed bearings for dust protection and long life
- Overall fork length: 32'
- Fork lowered height: 3"
- Fork raised height: 9'
- Overall dimensions: 64" W x 50" L x 51" H
- Usable straddle width is 50" between outriggers
- Rear wheel diameter: 10"
- · 90-day limited warranty





Model	Capacity	Overall	Wt.
No.	lbs.	Fork Width	lbs.
MN461	2000*	9 1/2" - 26"	239
MN462	2500**	10" - 26 3/4"	457
MN463	Optional Tow B	ar Package	20

- * 2,000 lbs. at 12"" horizontal load center, 1,500 lbs. at 15"" and 1,000 lbs at 24"".
- ** 2,500 lbs. at 12"" horizontal load center, 2,000 lbs. at 15"" and 1,500 lbs at 24"".

QUICK LIFT HYDRAULIC PALLET TRUCKS

- Maximize operator efficiency with this quick-lift pallet truck
- Lifts to full height with only four pumps when empty
- 2-speed pump automatically switches to low-speed operation
- Allows forks to quickly rise to upper pallet boards for quicker operation
- Each fork measures 6 1/4" wide
- · Poly-on-steel wheels are the best in the industry
- · 90-day limited warranty





Model	Fork	Height	Frame	Fork	Capacity	
No.	Lowered"	Raised"	Width"	Length"	lbs.	
MN365	3	7 1/2	20	48	5500	
MN366	3	7 1/2	27	48	5500	

PALLET TRUCK CADDY

- · Durable molded plastic
- Economical product will convert a standard pallet truck into a portable workstation in minutes
- Overall dimensions: 16 1/4" W x 7 3/4" D x 18 5/8" H
- Includes: Tool pockets on each side, pen and pencil tray, clipboard holder, built-in cup or can holder, and storage compartment

Model No. MN368





POWER-START TECHNOLOGY™ PALLET TRUCKS


THE RIGHT TOOL FOR ERGONOMIC PALLET MOTION!

- Reduces starting resistance even when truck is heavily loaded
- Select travel direction via option on handgrip, squeeze the handgrip, pump the tow bar and the truck is launched in the walking direction
- When handgrip is pressed downward, and tow bar raised, the truck is launched in the direction of the forks
- 2-year limited warranty

Specifications:

- Forks: 27" W x 48" L
- Minimum fork height: 3"
- Maximum fork height: 7 1/2"
- Rated capacity: 5000 lbs.
- Weight: 188 lbs.
 Model No. MH736








LIFT-RITE® TITAN PALLET TRUCKS

- New one-piece pump for improved performance and reliability
- Includes ergonomic handles and articulating steering wheels
- 7" wide forks
- Fork lowered height: 3"
- Fork raised height: 7 3/4"
- 2-year limited warranty





Custom sizes available

UNIVERSAL PALLET TRUCK FOOTGUARDS

- Steel construction with powder-coat finish
- Prevents crushed toes and other foot injuries
- Universal design fits most manual hand pallet trucks
 Wraparound guard, floats up and down allowing
- for use on dock levelers and dock plates
- Offers full range of motion and does not interfere with normal pallet truck operation
- Width: 8"

Model No. MN367







LIFTING EQUIPMENT

FORK EXTENSIONS

- · Handle large and odd shaped loads with increased stability and minimum damage
- Available in 4", 5" and 6" fork widths, lengths are from 54" to 96"
- · Easy to use slide-on design
- Fork fits up to 2" thick
- · Convenient on/off design · Locking bar keeps
- extensions in place Fork extension not to exceed 50% more than existing fork length





Model No.	Accommodates Fork Width"	Fork Extension Overall Width"	Length"	Max. Fork Thickness"	Wt. Ibs.
MF775	4	5	54	2	84
MF776	4	5	63	2	98
MF778	4	5	84	2	124
MF781	5	6	54	2	96
MF782	5	6	63	2	110
MF784	5	6	84	2	129
MF785	5	6	96	2	158
MF787	6	7	54	2 1/2	104
MF788	6	7	63	2 1/2	116
MF789	6	7	72	2 1/2	134
MF790	6	7	84	2 1/2	156
MF791	6	7	96	2 1/2	181

Also available: Add-on for optional pins style fork extension and other lengths.

WALL BRACKETS

- · All welded heavy-duty
- To keep fork extensions out of the way when not in use
- One wall bracket required for each pair of forks
- Kleton safety yellow




Model	Dimensions	Wt.
No.	W" x H"	Ibs
ML282	6 x 8	5

Hardware not included



FORK EXTENSIONS

- Handle large and odd shaped loads with increased stability
- Easy to use slide-on design
- Steel retaining strap prevents extensions from sliding off forks during use
- Fork extension not to exceed 50% more than existing fork length
- Available in 4" and 5" fork widths, with lengths of 72" and 96"







Model No.	Accommodates Fork Width"	Fork Extension Overall Width"	Length"	Wt. Ibs.
ML346	4	5	72	105
ML347	5	6	72	116
ML348	4	5	96	140

CABLE REEL ROLLERS

- · All welded, ready to use
- For winding or dispensing cable, chain, wire, rope and hose
- Turns reel handling into a one person operation
- Accommodates unlimited reel widths and all reel diameters, flanges up to 5 1/2" thick
- Rear roller adjusts to six positions
- Heavy-duty side rollers eliminate slipping or wedging between rollers and reel
- Inclined ramp permits easy loading and unloading
- Dimensions: 28" L x 9" W x 4 1/4" H
- Capacity: 3000 lbs in pairs
- Weight: 58 lbs/pair
- Must be anchored to floor
- Durable Kleton blue enamel finish

Model No. MD166









WINCH-OPERATED **EASY-LIFTS**

- · Ideal for use in factory, office or shipping department
- functions from lifting objects and positioning production at best working height, to moving light loads without tying up heavy equipment
- forks allow the shop lifter



SPECIFICATIONS:

Capacity:	500 lbs. at 10" load centre
Overall height:	60"
Platform size:	20" x 20"
Lowered platform height:	4 1/2"
Lift above floor:	52"
Wheels:	6" diameter
Swivel Casters:	3" diameter
Weight:	98 lbs.
Model No. MA479	

HYDRAULIC STACKERS

- Allows workers to manoeuver and lift heavy loads safely to comfortable needed height
- Front 5" and rear 4" phenolic casters allow loads to be moved easily
- Stacker comes standard with floor locks, safety screen and foot guards for safety



SPECIFICATIONS:

Capacity:	1000 lbs. at 15" load center
Overall dimensions:	25.5" W x 40" D x 80" H
Platform size:	24" x 24"
Lowered platform height:	5 3/4"
Raised platform height:	68"
Base legs:	15" inner, 21" outer
Wheels:	5" front, 4" rear
Weight:	234 lbs.
Model No. MH690	

HYDRAULIC STACKER

Allow workers to manoeuver and lift heavy loads safely to comfortable needed height

Foot pedal folds safely out of the way Front 5" polyurethane casters and rear 3" polyurethane wheels allow loads to move easily





SPECIFICATIONS: Capacity: Lowered platform height:4" Raised platform height: 60" Model No. MN397

LIFTING EQUIPMENT & DOLLIES

HYDRAULIC STACKERS


- · Rugged frame construction
- Solid steel adjustable forks
- · Designed for pallet loading and removal from racking storage even in the smallest storage spaces
- · Straddle length: 42"
- Fork length: 42"
- · Load centre: 24"
- · Manually propelled with electric powered hydraulic lift
- · Battery-powered is standard (AC power available)
- · Automatic built-in battery charger included
- Other capacities available


PLEASE SPECIFY WHEN ORDERING:

Single stage stacker between 38" and 50" Telescopic stacker between 42" and 54"

Note: Inside straddle dimension is recommended to be 2" greater than the overall pallet width (outside straddle is 6" greater than straddle inside dimension).







TELESCOPIC (TWO STAGE) STACKERS

Model No.	Clearance of Top Mast"	Raised Height of Top Forks"	Capacity lbs.	Wt. Ibs.
LT398	70	96	1500	815
LT399	82	120	1500	875
LT400	88	132	1500	900
LT401	94	144	1500	924

Other dimensions and capacities available

SINGLE STAGE STACKERS

Model No.	Clearance of Top Mast"	Raised Height of Top Forks"	Capacity lbs.	Wt. Ibs.
LT395	72	60	1500	625
LT396	82	70	1500	638
LT397	92	80	1500	652

Other dimensions and capacities available

PALLET CAROUSELS

Loading and unloading operations that originally required a large amount of time can be done more efficiently with less fatigue and risk of back injury. The carousel may be added to an existing workbench, scissors table or simply placed on the floor. This Lazy Susan concept is constructed from two pieces of rolled structural angle. A series of roller bearings transfer the load smoothly and evenly to the supporting surface. Overall height is 2".

Model No.	Outside Diameter"	Capacity lbs.	Wt. lbs.	
MH204	40	2000	43	
MH205	40	4000	47	
MH206	40	6000	47	

Model No.	Outside Diameter"	Capacity lbs.	Wt. Ibs.	
MH207	48	2000	51	
MH208	48	4000	57	
MH209	48	6000	69	





PRY DOLLIES

- · Move heavy boxes, die blocks and machinery
- Heavy-duty nose plate gets under the load, 6' steel or wooden handle gives tremendous leverage
- Come with 5" x 2" poly-on-steel casters



Model No.	Handle	Nose Plate"	Cap. Ibs.	Wt. Ibs.
MF870	Wood	6 x 31/8	4250	32
MF871	Steel	6 x 31/2	5000	42

ALUMINUM DECK DOLLIES

- 3/8" aluminum treadplate construction, countersunk bolts
- Four bolted-on 4" swivel non-marking rubber casters



Model	Dimensions		Wt.	
No.	W"	x	D"	lbs.
MA196	18	Х	18	25
MA197	18	Х	24	27
MA198	24	Х	24	30

MACHINERY MOVERS & ROLLERS

LIGHT-DUTY SERIES ROLLERS

- Featuring an endless chain action design and comes in either rigid or swivel tops
- Both versions available topped with rough, rugged non-slip pads or smooth top style, ideal for permanent mounting applications

 Light duty series rollers are low and have high capacity



Model	Cap.			Di	mensio	ons		Wt.
No.	Tons	Top Style	L"	X	W"	X	H"	lbs.
MA802	3/4	Swivel Padded	6 1/2	Х	3 5/8	Х	3 5/16	9
MA825	2	Swivel Padded	6 1/2	Х	4 1/8	Х	3 15/16	15
MD551	3/4	Swivel Smooth	6 1/2	Х	3 5/8	Х	3	9
MD552	2	Swivel Smooth	6 1/2	χ	4 1/8	Х	3 9/16	15
MA801	3/4	Rigid Padded	6 1/2	χ	3 5/8	Х	3	9
MA824	2	Rigid Padded	6 1/2	Х	4 1/8	Х	3 9/16	15

LIGHT-DUTY RIGGER KITS

3 TONS TO 8 TONS

- Kits contain two steering handles and four padded rollers offered with four swivel tops or two swivel and two rigid tops
- Sturdy steel carrying case stores all items and measures 16" L x 12 3/8" W x 4 3/8" D
- · Handles knock down to fit in case

Model No.	Capacity Tons	Kit Contents	Wt. Ibs.
MA879	3	4 x MA802 Swivel Top	55
MA875	3	2 x MA802 Swivel, 2 x MA801 Rigid Top	43
MA887	8	4 x MA825 Swivel Top	85
MA876	8	2 x MA825 Swivel, 2 x MA824 Rigid Top	83



TOE JACKS

- · Strong, portable and safe
- · Lifts loads with only 1" ground clearance
- 5 and 10-ton models operate horizontally and vertically
- Base, toe and pump assembly swivel independently of each other
- Perfect complement to any Hilman roller



Model No.	Max Lifting Height	Pick-Up Position At Base	Capacity Tons	Wt. Ibs.
MH825	8.24	1.06	5	44
MH826	9.32	1.06	10	64
MH827	9 32	2 16	25	203

TRI-GLIDE 3-POINT MOVING SYSTEMS

6 TONS TO 18 TONS

- Tri-Glide 3-point moving system is designed for moving heavy loads over specially coated floors
- Comprised of a front steering unit and two rear adjustable units
- Additional modules can be added to further stabilize large, bulky loads
- Developed in response to a growing demand for floor protection when moving heavy loads over smooth, painted, finished, or sealed floors



Model	Cap.	Roll	Dimensions Front Unit			Rear Unit	Wt		
No.	Tons	Material	L"	x	W"	X	H"	Width Adj."	lbs.
MH768	6	Nylon	21 1/16	Х	18 1/2	Х	4	10-48	186
MH769	12	Nylon	23 1/8	Χ	18 1/2	Х	4	14-48	215
MH770	18	Nylon	25 5/8	X	18 1/2	Х	4	19-48	24

DELUXE KITS

15 TONS TO 60 TONS

- Rugged kits are preferred by many professional riggers and movers
- Use them at the job site, in the factory, to solve your heavy load moving problems
- Steel chain-action rollers are perfect for machinery and equipment moves and convenient to have in every tool crib
- Kits include four locking rollers with either padded or diamond steel tops and two steering handles (four preload pads are included with diamond top kits)
- Kit cases are lockable and have sturdy lifting grips for easy handling



Model No.	Capacity Tons	Kit Contents	Wt. Ibs.
MA878	15	4 x MA839 Padded Tops	196
MA877	15	4 x MA838 Diamonds, 4 x Preload Pad Tops	196
MA881	30	4 x MA863 Padded Tops	208
MA880	30	4 x MA862 Diamonds, 4 x Preload Pad Tops	208
MA883	40	4 x MA805 Padded Tops	212
MA882	40	4 x MA804 Diamonds, 4 x Preload Pad Tops	212
MA885	60	4 x MA812 Padded Tops	248
MA884	60	4 x MA811 Diamonds, 4 x Preload Pad Tops	252

BOLT-ON ROLLERS

- Oversized tops enable them to be bolted or welded to heavy load
- Work equally well upside down or right side up
- Ideal for applications requiring permanent or semi-permanent mounting (linear motion, bearing slides, heavy casters, or conveyors)





Model	Capacity	Dimensions				Wt.	
No.	Tons	L"	x	W"	x	H"	lbs.
MA800	3/4	6 1/2	Х	7	Х	3 1/4	12
MA826	2 1/2	6 1/2	Х	7	Х	3 5/8	21
MA850	5	8	Х	8	Χ	3 1/8	22
MA810	15	10 5/8	Х	10	Х	3 7/8	46
MA827	20	10 5/8	Х	10	Х	3 7/8	49
MA849	37 1/2	15	Х	12	Х	5 1/2	121
MA867	75	21	Х	14	Х	6 3/4	241

MOVING SUPPLIES

POLYETHYLENE TARPAULINS

- Reinforced polypropylene rope sewn-in welded hems
- Heavy-duty rust resistant grommets every 3'
- · Increased UV resistance for long life
- · Water resistant coating
- Finished sizes may vary due to hem allowance

STANDARD-DUTY BLUE

- · 8 x 8 weave density
- 100-micrometres thick (4 mil)

HEAVY-DUTY WHITE

- 10 x 10 weave density
- 150-micrometres thick (6 mil)
- Four corner patches


INDUSTRIAL GREEN/SILVER

- 14 x 14 high density weave
- 225-micrometres thick (9 mil)
- 9" x 9" triple layered on four corners

SUPER HEAVY-DUTY SILVER

- 16 x 16 high density weave
- 300-micrometres thick (12 mil)
- 9" x 9" triple layered on four corners
- Silver side provides heat and UV light diversion





KILETON

		Mode	l No.	
Dimensions'	Standard-Duty Blue	Heavy-Duty White	Industrial Green/Silver	Super Heavy-Duty Silver
5 x 7	NI768	-	-	-
6 x 8	NI769	N1780	JB567	-
8 x 10	N1770	NI781	JB568	JC626
10 x 12	NI771	NI782	JB569	JC627
10 x 20	NI772	-	-	-
12 x 16	NI773	NI783	JB570	-
16 x 20	NI774	NI784	JB571	JC628
18 x 24	NI775	JC512	-	JC629
20 x 30	N1776	JC513	JB572	JC630
24 x 30	N1777	NI785	-	JC631
30 x 40	NI778	JC514	JC516	JC632
30 x 50	JC510	JC515	JC517	JC633
30 x 60	-	-	-	JC634
40 x 50	JC511	JC625	JC518	-
40 x 60	NI779	JB508	JB573	JC635

INSULATED TARPAULINS

- · Lightweight and flexible, moisture resistant insulated tarpaulin
- Manufactured with 3/16" closed cell polyethylene foam insulation
- · R-value is maintained in damp cold conditions
- Durable, water resistant polyethylene shell
- Heavy-duty rust resistant grommets every 2'
- R value: 1.0
- Dimensions: 12' x 20'

Model No. JD420

CLEAR TARPAULINS

- Polyethylene tarpaulin with reinforced nylon gridding
- Water and mildew resistant coating
- Heavy-duty rust resistant grommets
- 3 x 3 weave density
- 200 micrometers (8-mil) thick
- Finished sizes may vary due to hem allowance



Model No.	Dimensions'				
JD414	8	Х	10		
JD415	10	Х	12		
JD416	16	Х	20		
JD417	20	Х	30		
JD418	30	Х	40		
JD419	40	Х	60		

FURNITURE PADS

- · Protect furniture from scratches when moving
- Zigzag stitching provides durability and consistent cushioning
- · Cotton and polyester material
- 72" W x 80" L

PREMIUM FURNITURE PADS

- 40-oz. filling
- Dark blue/light blue
- Weight: 5.5 lbs.

Model No. PF460

STANDARD FURNITURE PADS

- · 29-oz. filling
- Dark blue/green
- Weight: 5 lbs.

Model No. PF461



STRAP-ALL™ ONE INCH STRAPS

- Ratchet strap with ratchet
- Light-duty tie-down can be used on pick-up trucks utility trailers, car top racks and boat trailers





Model	Strap	Breaking	Working Load
No.	Length'	Strength lbs.	Limit lbs./kg
ND361	16	1200	835/380

2" LOGISTIC STRAPS

- Designed to take care of most interior van loading requirements
- Standard 48" fixed end
- · Adjustable captive end to avoid loss or theft
- · Comes with ratchet buckle and webbing
- Spring-loaded "E"



	KINEDYNE
--	----------

Model Strap		rap	Breaking	Working Load Lir		
No.	Length'	Width"	Strength lbs.	Colour	lbs./kg	
ND352	12	2	3000	Gold	1000/455	
ND353	16	2	3000	Grey	1000/455	
ND354	20	2	3000	Blue	1000/455	

RUBBER TIE DOWNS

- · Retains its rebound qualities
- · Rot resistant
- Zinc-plated steel hooks

Nodel No.	Length"	Model No.	Lengt
E366	5	PE369	21
E367	9	PE370	31
E368	15	PE371	41



10-PC. BASIC TIE DOWN SET

Model No. PF090 Set contains: 4 PE369, 2 PE370 and 4 PE371

16-PC. ALL-PURPOSE TIE DOWN SET

Model No. PF091 Set contains: 2 PE367, 2 PE368, 4 PE369, 4 PE370 and 4 PE371



Model No. PF092 Set contains: 10 PE369 and 10 PE371



HARDWOOD DOLLIES

- Countersunk bolts prevent scratches
- Wood thickness: 7/8"
- · Rounded edges and handles facilitate storage and movability
- Non-marking casters
- · Shipped knocked down







REPLACEMENT CASTERS

Model No.	Description
ML391	3" Swivel Polyolefin
ML044	3" Swivel Polyurethane
ML393	4" Swivel Polyolefin
ML333	4" Swivel Blue Elastic Rubber
ML045	4" Swivel Polyurethane

CHOOSE FROM THREE CASTER TYPES







4" Blue Elastic Rubber

Model	Dimensions	Caster		Capacity
No.	W" x D"	Type	Caster"	lbs.*
ALL WC	OOD			
MN189	18 x 24	Polyolefin	3	900
MN195	18 x 24	Polyurethane	3	900
MN201	18 x 24	Polyolefin	4	1000
MN213	18 x 24	Blue Elastic	4	1400
MN207	18 x 24	Polyurethane	4	1600
MN192	18 x 30	Polyolefin	3	900
MN198	18 x 30	Polyurethane	3	900
MN204	18 x 30	Polyolefin	4	1000
MN216	18 x 30	Blue Elastic	4	1400
MN210	18 x 30	Polyurethane	4	1600
CARPE	TED ENDS			
MN190	18 x 24	Polyolefin	3	900
MN196	18 x 24	Polyurethane	3	900
MN202	18 x 24	Polyolefin	4	1000
MN214	18 x 24	Blue Elastic	4	1400
MN208	18 x 24	Polyurethane	4	1600
MN193	18 x 30	Polyolefin	3	900
MN199	18 x 30	Polyurethane	3	900
MN205	18 x 30	Polyolefin	4	1000
MN217	18 x 30	Blue Elastic	4	1400
MN211	18 x 30	Polyurethane	4	1600
RUBBER	RENDS			
MN191	18 x 24	Polyolefin	3	900
MN197	18 x 24	Polyurethane	3	900
MN203	18 x 24	Polyolefin	4	1000
MN215	18 x 24	Blue Elastic	4	1400
MN209	18 x 24	Polyurethane	4	1600
MN194	18 x 30	Polyolefin	3	900
MN200	18 x 30	Polyurethane	3	900
MN206	18 x 30	Polyolefin	4	1000
MN218	18 x 30	Blue Elastic	4	1400

Polyurethane

WOOD DOLLY RACKS

- · Convert a basic wood dolly into a multi-purpose panel caddy
- All-welded 1" tube design for durability
- Tubular steel rack is padded to prevent scratching or marring
- Durable Kleton blue enamel finish



Wood dolly not included



Model		Wt.
No.	Description	lbs.
MD549	Use with Wood Dolly 18" x 24"	12
MD550	Use with Wood Dolly 18" x 30"	15

STEEL DECK DOLLIES

- Heavy-duty, all-welded 14-gauge steel deck
- Four bolted-on 4" swivel
- non-marking rubber casters
- MA199 Optional 34" long steel T-handle for ease of movement under full loads
- Capacity: 1200 lbs. evenly distributed
- Caster assembly required
- Durable Kleton blue enamel finish





Model		Dimensions							
No.	W"	X	D"	X	H"	lbs.			
MA242	18	Х	18	Х	7	23			
MA243	18	Х	24	Χ	7	25			
MA244	24	χ	24	Х	7	27			
MA199		34" Handle							

ANGLE FRAME DOLLIES

- Heavy-duty all-welded 1 1/2" x 1 1/2" x 1/8" angle frame construction
- Four bolted-on 4" swivel non-marking rubber casters
- · Capacity: 1200 lbs. evenly distributed
- · Caster assembly required
- · Durable Kleton blue enamel finish



Model		Din	Wt.				
No.	W"	X	D"	X	Н"	lbs.	
MA190	18	Х	18	Х	7	23	
MA191	18	x	24	x	7	25	



18 x 30

MN212

* Evenly distributed

Model		Din		Wt.		
No.	W"	X	D"	x	H"	lbs.
MA192	24	χ	24	Х	7	27
MA193	24	χ	36	Х	7	30

MA194

PREMIUM HARDWOOD DOLLIES

MEDIUM-DUTY

• 7/8" wood top; countersunk bolts

1600

- Carpeted dolly will prevent marks and scratches on equipment being moved
- 3" polyolefin casters
- Capacity: 900-lbs. evenly distributed
- Shipped knocked down

HEAVY-DUTY

- 13/4" wood top (2 x 1 1/16" pieces); countersunk bolts
- Carpeted dolly will prevent marks/scratches on equipment
- 4" resilient non-marking casters
- Capacity: 1400 lbs. evenly distributed
- Shipped knocked down





Model No.	Dim. W" x D"	Platform Type	Wt. Ibs.
MEDIU	M-DUTY		
MA186	18 x 24	Standard	26
MA187	18 x 24	Carpeted	28
MD515	18 x 30	Standard	32
MD516	18 x 30	Carpeted	34



		,	,
Model No.	Dim. W" x D"	Platform Type	Wt. Ibs.
HEAVY	DUTY		
MA188	18 x 24	Standard	30
MA189	18 x 24	Carpeted	32
MD517	18 x 30	Standard	38
MD518	18 x 30	Carpeted	40

POLYETHYLENE DOLLIES

- · Modular, high-impact polyethylene design
- Won't splinter, swell or rot
- Round corners and edges with channel steel reinforced sides
- 4" polyolefin swivel casters
- · Capacity: 400 lbs.

Model	Dimensions					Platform	Wt.
No.	W"	X	D"	X	Н"	Type	lbs.
MA194	18	Х	30	Х	6	Flush Deck	21
MA195	18	X	30	X	6	Padded Rubber Deck	23



CUSTOMISE IT TO YOUR SPECIFICATIONS. **SEE PAGE B71 FOR DETAILS**

HAND TRUCKS

RUBBER WHEEL HAND TRUCKS

- Constructed of 1" 16-gauge steel tube
- 7-gauge steel nose plate
- Overall width: 19 1/2"Wheel dimensions: 8" x 2"
- · Powder coated finish



Model No.	Description	Nose Plate W"	Din x	nensions D"	Overall Height"	Capacity lbs.	Wt. Ibs.
MK728	Continuous Handle	14	Х	8 1/2	46	600	24
MK729	Dual Handle	14	Х	8 1/2	48	600	24
MN103	P-Handle	14	Х	9	51	600	24

REPLACEMENT PARTS & WHEELS

Model No.	Description	
ML812	Rubber Wheel	
MK993	Hand Grip	



- Constructed of 1" 16-gauge steel tube
- 8-gauge steel nose plate
- Overall width: 21 1/2"
- Wheel dimensions: 10" x 3"
- · Powder coated finish



Model		Nose Plate	Dim	ensions	Overall	Capacity	Wt.
No.	Description	W"	X	D"	Height"	lbs.	lbs.
MH300	Dual Handle	14	Х	10	46	600	23
MH301	Continuous Handle	14	Χ	10	48	600	26
MH302	P-Handle	14	Х	9	51	600	23

REPLACEMENT PARTS & WHEELS

Model No.	Description
ML810	Pneumatic Wheel
MK993	Hand Grip

FLAT FREE WHEEL HAND TRUCKS

- Constructed of 1", 16-gauge steel tubing
- Nose plate 8-gauge steel
- Overall width: 22"
- Wheel dimensions: 10" x 3 1/2"
- Powder-coated



Model		Nose Plate	e Din	nensions	Overall	Capacity	Wt.
No.	Description	W"	X	D"	Height"	lbs.	lbs.
MN389	Dual Handle	14	Х	10	46	600	20
MN390	Continuous Handle	14	Х	10	48	600	22
MN391	P-Handle	14	Х	9	51	600	22

REPLACEMENT PARTS & WHEELS

Model		
No.	Description	
MN378	Flat Free Wheel	
MK993	Hand Grip	

HEAVY-DUTY DUAL HANDLE HAND TRUCKS

- Constructed of 1 1/4" 14-gauge steel tube
- · 6-gauge steel nose plate
- Overall height: 46"Overall width: 20"
- Powder coated finish



Model No.	Description	Wheel Dimensions"		Nose Plate Dimensions W" x D"		Capacity lbs.	Wt. Ibs.		
MK731	Pneumatic Wheel	10	Х	3	14	Х	8	800	36
MK730	Rubber Wheel	8	Х	2	14	Х	8	1000	36

REPLACEMENT PARTS & WHEELS

Model		
No.	Description	
ML813	Rubber Wheel	
ML811	Pneumatic Wheel	
ML030	Hand Grip	









HEAVY-DUTY SPADE TRUCKS

- · All welded, ready to use
- Constructed of double-welded
 1 1/4" round 14-gauge steel tubing
- Oversized nose plate and easy grip frame helps with the balancing of larger items
- Tapered 22" L x 13" D x 1/4" thick nose plate
- Two 10" mold-on rubber wheels
- · Capacity: 1200 lbs.
- · Durable Kleton blue enamel finish





Model	Dimensions	Wt.
No	W" x H"	Ibs.
ML324	22" x 53"	92

APPLIANCE TRUCKS

- · Move large appliances easily
- Heavy-duty all welded industrial construction
- Vinyl bumpers on face of truck to prevent damage to appliances
- Heavy-duty continuous stair climbers for easy climbing/descending
- 8" solid rubber wheels
- · Ratchet mechanism for easy fastening of loads
- Overall dimensions: 14 1/2" L x 24" W x 59" H
- · Capacity: 550 lbs.
- Weight: 46 lbs.

Model No. ML616



VENDING MACHINE APPLIANCE TRUCKS

- · Move large appliances easily
- Heavy-duty all welded industrial construction
- Vinyl bumpers on face of truck to prevent damage to appliances
- Heavy-duty continuous stair climbers for easy climbing/descending
- Fold out rear legs with two 4" swivel casters
- 8" solid rubber front wheels
- · Ratchet mechanism for easy fastening of loads
- Overall dimensions: 14 1/2" L x 24" W x 66" H
- · Capacity: 850 lbs.
- Weight: 65 lbs.

Model No. ML617



MOVING STRAPS

- Allows for safe movement of appliances and larger items
- Movers can constantly stay in an upright position during the move, reducing the risk of back injuries
- Nylon (5000 lbs. test)
- Includes: Two transport straps, 4"x 4', and two adjustable straps, 1 3/4" x 9'

Model No. MD223



HEAVY-DUTY DUAL HANDLE HAND TRUCKS

- Constructed of 1 1/4", 14-gauge steel tubing
- Nose plate 6-gauge steel
- Overall height: 46'
- Overall width: 20"
- 8" x 12" nose platePowder-coated





Model No.	Description	Wheel"	Capacity lbs.	Wt. Ibs.
MA376	Rubber Wheel	10 x 2	1000	40



DELUXE 12" NOSE PLATE HAND TRUCKS

- · All welded, ready to use
- Constructed of 1" round 14-gauge steel tubing
- · Transport short to tall loads easily
- P handle ideal for one hand control
- Strong 12" L x 14" D x 3/16" thick nose plate
 - Double welded 3/16" x 1 1/2" cross bars
- Add a folding nose extension
- to be able to transport larger loads
 Two 10" full pneumatic wheels
- · Capacity: 700 lbs.
- Durable Kleton blue enamel finish




Model No	Description	Overall Dimensions W" x H"	Wt. Ibs.
ML321	Lo-Boy	23 x 50	40
ML322	Hi-Boy	23 x 72	46
ML323	Nose Extension	12x 22" Nose Length	8

CONVERTIBLE DELUXE STEEL HAND TRUCKS

- Constructed of 1" round 14-gauge steel tubing
- Quickly converts from a 2-wheel hand truck to a 4-wheel platform truck
- 8" x 14" nose plate
- Comes with two welded-on stair glides
 To a 10" fell and a second secon
- Two 10" full pneumatic wheels and two 3" bolted-on casters
- Capacity: Hand truck 600 lbs.
 Platform truck 800 lbs.
- Durable Kleton blue enamel finish





HAND TRUCKS WITH SWIVEL CASTERS

- 4" rear poly casters allow small diameter turns in tight areas
- Combination two handle and utility bar design reduces strain of lifting, lowering and transporting
- 8" deep nose plate
- 10" x 2 3/4" semi-pneumatic front wheels
- Overall dimensions: 20 1/2" W x 47 1/2" H
- Capacity: 800 lbs.
- Weight.: 53 lbs.
 Model No. MD758





HAND TRUCKS

NYLON FRAME HAND TRUCKS

STRONG AS STEEL, LIGHTER THAN ALUMINUM

- Long fibre nylon frame will not mar products or damage goods
- Stair glides integrate into frame
- Aluminum loop handles, 14" W x 8" D nose plate
- Frame width: 12"
- · Capacity: 500 lbs.





STATE IS DE-				
Model No.	Wheel Type	0.A. Height"	Wt. lbs.	
FLAT BACK FF	RAME			
MN268	10" Rubber	52	21	
MN269	10" Pneumatic	52	19	
CURVED BAC	K FRAME*			
MN270	10" Rubber	52	21	
MN271	10" Pneumatic	52	19	

^{*}Handles cylindrical or flat beds

NYLON LITE HAND TRUCKS

- · Lighter than aluminum trucks
- Glass-filled nylon frame will not mark products or damage goods
- Steel handle, 14" W x 7" D steel base plate
- 10" x 3 1/2" pneumatic tires
- Frame width: 12"
- · Overall height: 48"
- Capacity: 500 lbs.
- · Weight: 22 lbs.

Model No. MD642



CONVERTIBLE NYLON LITE TRUCKS

- Lighter than equivalent aluminum trucks
- Glass-filled nylon frame
- Steel handle and 14 1/2" W x 7" D steel base plate
- Converts in seconds from 2-wheel hand truck to 4-wheel platform truck
- 5" swivel casters, 10" x 3 1/2" pneumatic wheels
- 12" frame width and 20 1/2" overall width
- Capacity: 600 lbs., two wheels; 700 lbs., four wheels





Model	Hand	Truck	Platfori	m/Truck	Wt.
No.	Cap. lbs.	Height"	Length	Height"	lbs.
MD643	600	49 1/2	40	36	25

CURB RAMP

- · Light, portable and easy to handle
- Dimensions: 27" x 27'
- Capacity: 600 lbs.

Model No. MH224





LOAD RETENTION HAND TRUCKS

- Constructed of 1" round 14-gauge steel tubing
- 18 1/2" x 53" load retention grill to safely handle wide and awkward loads
- 7-gauge steel nose plate
- 18 1/2" W x 9 3/4" D nose plate
- Two 10" full pneumatic wheels
- · Capacity: 600 lbs.
- Durable Kleton blue enamel finish

Model No. MN412







FOLDING HAND TRUCKS

- · Lightweight and durable aluminum construction
- Convenient folding design permits storage in small spaces
- Comfortable ergonomic handle
- Elastic straps help to secure load
- Non-marking and shock-absorbing rubber wheels
- Capacity: 175 lbs. evenly distributed
- Weight: 8.75 lbs.



Model No.	Extended Dimensions"	Folded Dimensions"	Nose Plate W" x D"	Wheel Dimensions"
ML447	39 5/8 x 15 1/2 x 16 1/2	25 x 15 x 2 3/8	15 1/4 x 11	5 x 1 1/4

ALUMINUM STAIR CLIMBING HAND TRUCKS

- Battery-powered stair climbing hand trucks help reduce worker fatigue and the risk of injury, as well as reduce the number of employees needed to deliver cargo
- Pivoting and fixed ergonomic handle configurations available to handle a wide variety of cargo
- · Lift wheels are uni-directional to help prevent cargo from accidentally rolling down the stairs
- Dual speed control on all models to fit your application
- $\bullet \ \ \, \text{Electronic overload protection protects operating components if capacity is exceeded} \\$
- Grooved 16 1/2" W x 13 1/3" D nose plate provides superior grip to hold load in place
- 10" pneumatic wheels
- Capacity: 375 lbs.
- Quick-change battery and charger included





MN247

MN248

MN249

MN250

Model	Frame	Dimensions		
No.	Type	W"	X	H"
MN247	Ergo	18 1/2	Х	63
MN248	Fold	18	Х	61 (40 Folded)
MN249	Uni	17 1/2	Х	59
MN250	Fold-L	19	Х	64 1/2 (51 Folded)

Note: Each unit is capable of being customized with various options (i.e. wheel type and nose plate size). Also available in 240-lb. and 300-lb. capacities.

ALUMINUM HAND TRUCKS

CONVERTIBLE HAND TRUCKS

- Lightweight aluminum construction
- Converts easily from a 2-wheel hand truck to a 4-wheel platform truck
- 5" polyurethane casters and 10" flat free wheels
- · Shipped assembled



Model	Nose Plate	Hand Truck		Platform	Wt.	
No.	W" x D"	Cap. lbs.	Height"	Cap. lbs.	L" x W"	lbs.
ML621	18 x 10	600	52	1250	12 x 43	54



ALUMINUM HAND TRUCKS

- · Strong lightweight hand truck provides exceptional durability and versatility



	Model		se Pla		Overall		Wt.
	No.	W"	X	D"	Height"	Wheels	lbs.
A.	MN024	14	Х	7 1/2	48	8" Mold-On	17.5
B.	MN025	18	Х	7 1/2	48	8" Mold-On	20.5
С.	MN026	14	Х	7 1/2	52	10" Pneumatic	21.5
D.	MN027	18	Х	7 1/2	48	8" Mold-On	20
E.	MN028	18	Х	7 1/2	52	10" Pneumatic	23
E.	MN029	18	Х	7 1/2	52	10" Flat-Free	20
F.	MN030	14	Х	7 1/2	52	10" Pneumatic	22
G.	MN031	18	Х	10	52	10" Pneumatic	26.5
G.	MN032	18	Х	10	52	10" Flat-Free	23
Н.	MN033	18	Х	7 1/2	52	10" Pneumatic	23.5
I.	MN034	14	Х	7 1/2	48	10" Flat-Free	20

HAND TRUCK ACCESSORIES



FRAME EXTENSIONS





Model No. MN021

• Size: 23" Model No. MN022

STAIR CLIMBERS



Model No. MN015

NOSE EXTENSIONS

Only compatible with cast nose plates





• Size: 20"

Model No. MN019

• Size: 27" Model No. MN020

REPLACEMENT WHEELS







· 10" Pneumatic Model No. MN012

8" Mold-On Rubber • 10" Flat-Free Model No. MN013

Model No. MN014

ALUMINUM HAND TRUCKS

BUILD YOUR OWN HAND TRUCK IN 4 EASY STEPS



STEP 1: SELECT YOUR HANDLE



rubber sleeve Model No. ML997



Standard loop Model No. ML998



Vertical loop Not for use with MN006 and MN007 Model No. ML999



 Double grip Model No. MN001



Single grip Model No. MN002



Double "P' Model No. MN003

STEP 2: SELECT YOUR FRAME



· Straight frame Model No. MN004



Straight frame with large cross bar

Model No. MN005



Curved back frame Model No. MN006



Model No. MN007



STEP 3: SELECT YOUR NOSE PLATE



- Cast nose plate
- Dimensions: 14" x 7 1/2"

Model No. MN008



- Cast nose plate
- Dimensions: 18" x 7 1/2"

Model No. MN009



- Extrude nose plate
- Dimensions: 18" x 7 1/2"

Model No. MN010



- Extrude nose plate • Dimensions: 18" x 10"

Model No. MN011

STEP 4: SELECT YOUR WHEEL ASSEMBLY

Assembly includes two wheels, two axle brackets and one axle



• 8" Mold-On rubber Model No. MN035



Model No. MN036



• 10" Flat-Free Model No. MN037



ALUMINUM HAND TRUCKS

GEMINI® CONVERTIBLE ALUMINUM TRUCKS • Converts in seconds from a 2-wheel hand truck to a 4-wheel platform truck

- Lightweight, high strength aluminum construction
- Balanced to assure easier wheeling and positive load control
- 18" W x 7 1/2" D rugged cast aluminum noseplate
- 5" swivel casters; 10" x 3 1/2" full pneumatic wheels
- 16 5/8" frame width, 20 1/2" O.A. width
- Shipped knocked down

MAGLINER®

Model	Model Hand Truck			Platforn	Platform Truck			
No.	Gemini	Cap.	Ht."	Cap.	Ht."	Lgth."	lbs.	
MA319	Jr.	500 lbs.	51	1000 lbs.	40	38	44	
MA320	Sr.	500 lbs.	61	1000 lbs.	45 1/8	51	45	

OPTIONAL SNAP-ON DECK

Model No.	Description	Wt. lbs.
MB198	43 1/4" for Gemini Jr.	5
MB197	56" for Gemini Sr.	6

ALUMINUM HAND TRUCKS

- Strength, durability and versatility in a lightweight truck
- Totally modular trucks have no welds to break
- 500-lb. capacity on all models
- Shipped knocked down

MAGLINER®

	Model No.	No W"	se Pl x	ate D"	Overall Ht."	Wheels	Wt lbs
ļ.							
Α.	MA250	14	Х	7 1/2	48	8" Mold-On	18
B.	MA269	18	χ	7 1/2	48	8" Mold-On	19
С.	MA275*	14	Х	7 1/2	48	10" Pneumatic	21
D.	MA258	14	Х	7 1/2	52	8" Mold-On	19
D.	MA255	14	Х	7 1/2	52	10" Pneumatic	21
E.	MA263	14	χ	7 1/2	48	8" Mold-On	21
E.	MA261	14	Χ	7 1/2	48	10" Pneumatic	24
F.	MA271	18	χ	9	48	8" Mold-On	19
F.	MA270	18	Х	9	48	10" Pneumatic	22
G.	MA266	18	Х	7 1/2	52	8" Mold-On	19
G.	MA265	18	Х	7 1/2	52	10" Pneumatic	22
Н.	MA268	18	χ	7 1/2	54	8" Mold-On	19
H.	MA267	18	Х	7 1/2	52	10" Pneumatic	22

^{*} Frame has a curved back for cylindrical or flat loads













FOLDING HAND TRUCK

- · Easy-to-use latch system may be engaged with one hand
- Heavy-duty construction
- Features a comfort grip handle
- · 8" mold-on rubber wheels
- 14" x 7" locking folding nose plate
- · Overall height: 48" Capacity: 500 lbs.
- Weight: 22 lbs.
- Model No. MN117





THREE-POSITION HAND TRUCK

- Can be used to transport all your needs, from general use items to bulky equipment
- 18" x 7 1/2" nose plate included
- Two 10" pneumatic wheels and two 5" polyurethane casters
- · Two wheel position:
- 500 lbs. capacity, overall height 51"
- · Four wheel position: 750 lbs. capacity, overall height 40"
- Weight: 43 lbs.



Y-CABLE BRAKE HAND TRUCK

- Provides safer load control and reduces operator's accumulated muscle strain
- Easy ergonomic self-equalizing brake actuators
- Stair climber included
- 18" x 9" nose plate
- 10" pneumatic wheels
- Overall height: 60"
- Capacity: 500 lbs.
- Weight: 38 lbs.





ALUMINUM TRUCKS

ALUMINUM PLATFORM TRUCKS

- 40% lighter on average, than steel or wood-and-steel platform trucks
- Corrosion resistant for extra long life
- Box frame made of high strength all-welded aluminum channel
 Corner sockets at both ends allow handles to be used on either end of the truck
- Rubber corner bumpers prevent damage to walls and furniture
- Wide variety of casters to suit any application



8" PNEUMATIC CASTERS

Platform Dimensions"	Capacity lbs.	Smooth Deck Model No.	Wt. Ibs.	Tread Plate Deck Model No.	Wt. Ibs.
24 x 36	1400	ML901	51	ML904	52
24 x 48	1400	ML902	55	ML905	57
30 x 60	1400	ML903	66	ML906	68

10" PNEUMATIC CASTERS

Platform Dimensions"	Capacity lbs.	Smooth Deck Model No.	Wt. Ibs.	Tread Plate Deck Model No.	Wt. Ibs.
24 x 36	1850	ML907	56	ML910	57
24 x 48	1850	ML908	60	ML911	62
30 x 60	1850	ML909	71	ML912	73

8" FLAT-FREE CASTERS

Platform Dimensions"	Capacity lbs.	Smooth Deck Model No.	Wt. Ibs.	Tread Plate Deck Model No.	Wt. Ibs.
24 x 36	1100	ML913	54	ML916	55
24 x 48	1100	ML914	58	ML917	60
30 x 60	1100	ML915	69	ML918	71

10" FLAT-FREE CASTERS

Platform Dimensions"	Capacity lbs.	Smooth Deck Model No.	Wt. Ibs.	Tread Plate Deck Model No.	Wt. Ibs.
24 x 36	1200	ML919	58	ML922	59
24 x 48	1200	ML920	62	ML923	64
30 x 60	1200	ML921	73	ML924	75

8" MOLD-ON RUBBER CASTERS

Platform Dimensions"	Capacity lbs.	Smooth Deck Model No.	Wt. Ibs.	Tread Plate Deck Model No.	Wt. Ibs.
24 x 36	2000	ML925	64	ML928	65
24 x 48	2000	ML926	68	ML929	70
30 x 60	2000	ML927	79	ML930	71

6" POLYURETHANE CASTERS

Platform Dimensions"	Capacity lbs.	Smooth Deck Model No.	Wt. Ibs.	Tread Plate Deck Model No.	Wt. Ibs.
24 x 36	3400	ML931	48	ML934	49
24 x 48	3400	ML932	52	ML935	54
30 x 60	3400	ML933	63	ML936	65

8" POLYURETHANE CASTERS

Platform Dimensions"	Capacity lbs.	Smooth Deck Model No.	Wt. Ibs.	Tread Plate Deck Model No.	Wt. Ibs.
24 x 36	4000	ML937	53	ML940	54
24 x 48	4000	ML938	57	ML941	59
30 x 60	4000	ML939	68	ML942	70



PLATFORM TRUCKS

STEEL DECK PLATFORM TRUCKS

Choose from a large selection of deck sizes and casters to suit any institutional and/or industrial application.

- Made of strong 14-gauge steel deck with a 2" folded bottom lip for extra strength
 Removable 1 1/4" tubular chrome handle can be
- inserted at either end of platform
 Two rigid and two swivel casters (assembly required, hardware is included)







CASTER WHEEL TYPES

Hi-Temp Nylon: Solid black nylon caster will not crush under heavy loads. Good for use on all types of surfaces from wood to concrete. Will tolerate temperatures from a low -28°C to a high of 230°C. Not affected by most corrosive chemicals.

Full Pneumatic: Air filled black rubber tire offers excellent shock absorbing properties. Smooth, quiet rolling over rough, uneven surfaces and outdoor terrain. Not recommended on floors with metal shavings or corrosive chemicals.

Mold-On Rubber: Molded rubber wheel bonded to a spoked cast iron core. The iron core gives it strength while the molded rubber provides easy, smooth and quiet rolling over rough terrain.

Non-Marking Rubber: Used for uneven surfaces and carpet areas. Its quiet rolling feature makes it ideal for both institutional and industrial applications. Will resist wet conditions and corrosive chemicals.

Polyolefin: Plastic wheel with high impact strength and non-chipping properties. Oil, grease and chemical resistant.

CASTER SELECTION:

To select the correct caster that is required for a specific application determine:

- 1) Platform size needed
- 2) Maximum load capacity it will carry
- 3) Type of floor surface it will roll on i.e., concrete, wood, tile etc...
- Floor condition i.e., smooth, uneven, wet, chemicals, metal shavings, temperature etc.

Model No.	Wheel Dia."	Wheel Type	Load Capacity/lbs.	Wt. lbs.
24" W X 36"	L PLATFORM TE	RUCKS		
MB232	6	Hi-Temp Nylon	1300	77
MB233	8	Hi-Temp Nylon	1400	87
MB234	8	Pneumatic	1000	79
MB235	6	Mold-On Rubber	900	88
MB236	8	Mold-On Rubber	1400	96
MB237	5	Non-Marking Rubber	1200	63
MB238	5	Polyolefin	900	61
24" W X 48"	L PLATFORM T	RUCKS		
MB240	6	Hi-Temp Nylon	1300	90
MB241	8	Hi-Temp Nylon	1400	100
MB242	8	Pneumatic	1000	92
MB243	6	Mold-On Rubber	900	101
MB244	8	Mold-On Rubber	1400	109
MB245	5	Non-Marking Rubber	1200	76
MB246	5	Polyolefin	900	74
30" W X 48"	L PLATFORM TI	RUCKS		
MD421	6	Hi-Temp Nylon	1300	96
MD422	8	Hi-Temp Nylon	1400	106
MD423	8	Pneumatic	1000	98
MD424	6	Mold-On Rubber	900	107
MD425	8	Mold-On Rubber	1400	115
MD426	5	Non-Marking Rubber	1200	82
MD427	5	Polyolefin	900	80
30" W X 60"	L PLATFORM TI	RUCKS		
MB248	6	Hi-Temp Nylon	1300	110
MB249	8	Hi-Temp Nylon	1400	120
MB250	8	Pneumatic	1000	112
MB251	6	Mold-On Rubber	900	121
MB252	8	Mold-On Rubber	1400	129
MB253	5	Non-Marking Rubber	1200	96
MB254	5	Polyolefin	900	94

HEAVY-DUTY PLATFORM TRUCKS

WOOD DECK PLATFORM

- Sturdy 2" x 2" angle iron frame, with hardwood decking
- Ideal for carrying objects that scuff by metal to metal contact
- Steel frame absorbs shocks and handles uneven/heavy loads

ALL-STEEL PLATFORM

- Heavy 11-gauge, reinforced channel formed deck arc welded for maximum strength and long lasting rigidity
- Ideal for loads up to 2500 lbs.

CASTER PLACEMENT

- Available in standard-corner or diamond-tilt pattern
- Diamond tilt pattern allows the truck to tilt-balance slightly on the center side casters, allowing the truck to turn on its own length



Standard Corner Placement



Diamond Tilt Placement





10" Pneumatic Wheels 1200 lbs. Cap. Model No.	8" Rubber Wheels 2000 lbs. Cap. Model No.	8" Hi-Temp Nylon Wheels 2500 lbs. Cap. Model No.	Platform Dimensions* W" x L"	Wt.
WOOD DECK				
MB256	MB296	MB130	24 x 48-C	115
MB258	MB298	MB133	24 x 48-T	120
MB264	MB304	MB138	30 x 48-C	135
MB266	MB306	MB141	30 x 48-T	140
MB267	MB308	MB142	30 x 60-C	145
MB270	MD332	MB145	30 x 60-T	150
MB279	MB320	MB155	36 x 72-C	180
MB282	MB322	MB157	36 x 72-T	190
MB284	MB324	MB166	48 x 96-C	280
MB286	MB326	MB169	48 x 96-T	300
STEEL DECK				
MB255	MB295	MB131	24 x 48-C	110
MB257	MB297	MB132	24 x 48-T	115
MB263	MB303	MB139	30 x 48-C	130
MB265	MD331	MB140	30 x 48-T	135
MB268	MB307	MB143	30 x 60-C	140
MB269	MB309	MB144	30 x 60-T	145
MB280	MB319	MB154	36 x 72-C	175
MB281	MB321	MB156	36 x 72-T	185
MB283	MB323	MB167	48 x 96-C	240
MB285	MB325	MB168	48 x 96-T	265

^{*} Suffix C after platform size signifies corner caster placement. T is diamond tilt.



CUSTOMISE IT TO YOUR SPECIFICATIONS.
SEE PAGE B71 FOR DETAILS

PLATFORM TRUCKS

HEAVY-DUTY PLATFORM TRUCKS

- Solid 7/8" hardwood deck with 5" x 1 5/8" hardwood sidewall
- · Easy to manoeuvre with 44" high handle

MB122


MB123

MB124

MB125

MB126





1 1/4" tubular

chrome handle!

PLASTIC PLATFORM TRUCKS

· HDPE-molded structural plastic for strength and long-term durability

36

- Lightweight, easy to clean, chemical resistant and resists damage from long-term exposure to weather conditions
- Non-skid deck surface
- · Removable steel handle
- Other caster options and capacities available upon request
- Caster assembly required



60


60

Model No.	Caster Type	Platform Size W" x L"	Deck Height"	Handle Height"	Capacity lbs.	Wt. Ibs.
MN428	8" Mold-On Rubber	24 x 48	11	39	2000	90
MN429	8" Mold-On Rubber	30 x 60	11	39	2000	117
MN430	8" Polyurethane	24 x 48	11	39	2500	79
MN431	8" Polyurethane	30 x 60	11	39	2500	106
MN432	10" Pneumatic	24 x 48	13	41	1200	84
MN433	10" Pneumatic	30 x 60	13	41	1200	111
MN434	10" Flat-Free	24 x 48	13	41	1000	85
MN435	10" Flat-Free	30 x 60	13	41	1000	117
MN436	8" Pneumatic	24 x 48	11	39	1000	79
MN437	8" Pneumatic	30 x 60	11	39	1000	106
MN438	8" Flat-Free	24 x 48	11	39	900	80
MN439	8" Flat-Free	30 x 60	11	39	900	107

HEAVY-DUTY PLATFORM TRUCKS

- · Ideal for moving large and heavy loads
- Ergonomic handle design improves control and worker safety
- Powder-coated steel handle with retainer
- clips prevents unintended removal
- Steel reinforced deck for enhanced durability Molded-in-tie-down slots for load security
- Textured deck for enhanced durability
- Perimeter deck channel retains small items
- Two rigid and two swivel casters
- Assembly required





WAGON TRUCKS

- · Fifth wheel steering makes these trucks easy to manœuvre under full loads
- 14 1/4" deck height
- 10" pneumatic wheels
- Capacity: 1000 lbs.
- Durable Kleton blue enamel finish





195

210

230

Wood Deck		Steel Deck		Platform Dim.
Model No.	Wt. lbs.	Model No.	Wt. lbs.	W" x L"
MD186	120	MD187	130	24 x 48
MD188	150	MD189	170	30 x 60
MD192	190	MD193	210	36 x 72

ERGONOMIC PLATFORM TRUCKS

- Ergonomic handle is placed at a comfortable working height to alleviate back strains
- Picking list holder eliminates the need to handle loose papers
- Deck is constructed from 14-gauge all welded steel with a turned down lip and reinforced channels
- Two rigid and two swivel 8" mold-on rubber casters
- 48" L x 24" W
- Capacity: 1200 lbs.
- Kleton powder coat finish

Model No. ML892







5TH WHEEL WAGON TRUCKS

- Ideal for moving heavy loads in manufacturing plants, warehouses, maintenance shops and outdoor environments
- Fifth wheel steering ensures tight turning radius and easy manoeuvrability
- Vinyl grip, powder coated "T" handle stays upright when not in use
- "T" handle is removable for towing capabilities (tow package sold separately)
- Steel reinforced deck for enhanced durability
- Molded-in tie-down slots for load security
- Textured deck channel and perimeter deck channel retains small items





Model					15	Caster	Capacity	Wt.
No.	W"	x	L"	x	H"	Type	lbs.	lbs.
ML585	24	Х	42 7/8	Х	16 3/4	10" Pneumatic	1200	60
ML586	24	Х	42 7/8	Х	16 3/4	10" Rubber	2000	60
ML587	24	Х	547/8	Х	17 1/2	12" Pneumatic	2000	71
ML588	24	Х	547/8	Х	17 1/2	12" Rubber	2000	71
ML589	30	Х	66 7/8	Х	17 1/2	12" Pneumatic	2000	88
ML590	30	Х	66 7/8	Х	17 1/2	12" Rubber	2000	88
ML591	40	Х	70	Х	48 5/8	12" Pneumatic	2000	125
ML592	40	Х	70	X	50 3/4	16" Pneumatic	2000	130
ML593		To	ow packa	ge		-	-	2.8

WAREHOUSE TRUCKS

MB327

INSTITUTIONAL PLATFORM TRUCKS

- · Ideal truck for institutional applications hospitals, restaurants, shopping centres, offices, industry and anywhere else a quiet ride and professional appearance is required
- 14-gauge steel deck with 2" lip underneath
- · Non-skid rubber surface means product will not shift during use
- Rubber corner bumpers protect walls and furniture
- 1 1/4" tubular chrome handle with end panel contains small packages

• 5" non-marking rubber casters for a smooth,



Model	Din	nensi	ons	Wt
No.	W"	x	L"	lbs.
MB190	24	Х	36	64
MB208	24	Х	48	70
MB207	30	Х	48	88
MB209	30	Х	60	100

FOLDING HANDLE PLATFORM TRUCKS



Model	Plati	form	Dim.	Handle	Cap.	Wt.
No.	W"	X	Ľ"	Height"	lbs.	lbs.
MK988	19	Х	29	33 1/2	400	28
MK989	23	Х	35	34 1/2	660	42

FOLDABLE PLATFORM TRUCKS

· Ideal when solid, portable platform truck is required · Interlocking aluminum frame has dual length platform:

16" W x 20" L or 16" W x 28" L; handle height is 32"

Standard with vinyl corner bumpers

• Folds down to a compact 16" W x 20" L x 9 1/2" H

Rolls easily on 5" rubber casters · Capacity: 300 lbs.

· Weight: 18 lbs.

Model No. MK990








SEMI-LIVE SKIDS

- · Ideal for temporary storage of materials
- Heavy 11-gauge steel deck with reinforced channels or 3/16" x 2" x 2" angle frame with hardwood deck
- 52" jack handle (sold separately) quickly engages skid and turns it into a portable truck that manoeuvres easily in confined areas



- Capacity: 2000 lbs.
- Durable Kleton blue enamel finish



Steel Deck Model No.	Wt. Ibs.	Wood Deck Model No.	Wt. Ibs.	Deck Height	Dimensions W" x L"
MB327	110	MB328	115	12	24 x 48
MB329	130	MB330	135	12	30 x 48
MB331	140	MB332	145	12	30 x 60
MB337	175	MB338	180	12	36 x 72
MB348	51" Lo	ong Jack Handle	30		

DEAD SKIDS

- Tough and durable platforms for temporary storage and handling of material
- Heavy 11-gauge steel deck with reinforced channels
- 3/16" x 2" x 2" angle frame with hardwood deck
- Available with steel or hardwood decks
- Four sturdy steel legs
- keep loads of the floor
- Can be stacked when not in use
- enamel finish





Model No.	Deck Dim. W" x L"	Platform Type	Deck Height"	Wt. Ibs.
ML071	24 x 48	Steel	6	110
ML072	24 x 48	Wood	6	115
ML073	30 x 48	Steel	6	130
ML074	30 x 48	Wood	6	135
ML075	30 x 60	Steel	6	140
ML076	30 x 60	Wood	6	145
ML077	36 x 72	Steel	6	175
MI 078	36 x 72	Wood	6	180

TRIPLETM TROLLEYS

- · Three position handle lets users push, pull or fold flat for space efficient storage
- Non-skid surface helps prevent load shifting
- Durable, structural foam deck won't rust, dent or bend
- Mark resistant casters give stability over rough surfaces





Model		Dimensions					Wt.		
No.	Description	W"	x	L"	X	H"	lbs.	lbs.	
MH708	Standard Trolley	20 1/2	Х	32 1/2	Х	37 3/4	500	25	

LIFT TABLES

HYDRAULIC SCISSOR LIFT TABLES

Kleton tables are available in various capacities and travels to satisfy a wide variety of applications. All models have an integrated hydraulic pump/cylinder assembly. The Kleton scissor lift tables add the value of mobility to the hydraulic lift table concept. Exceptional functionality and manoeuvrability is apparent, whether loaded or empty. In addition, rugged construction and premium-quality hydraulics complement their ease of use with low maintenance.


APPLICATIONS

Kleton tables are used in a wide variety of applications, from stocking shelves in retail stores to lifting and moving materials in warehouses, machine shops and manufacturing operations.

OPERATION

The Kleton design allows workers to easily move and position loads to a convenient working height. By minimising undesirable lifting, reaching and stretching,





STANDARD FEATURES

- · Heavy-duty construction with captured scissor rollers for maximum stability
- Superior hydraulic systems feature an integrated pump-cylinder for maximum reliability
- High quality casters and wheels for exceptional roll ability (two fixed, two swivel)
- Ergonomic push handle with convenient lowering control
- Lowering control automatically stops when released for added safety
- Convenient maintenance pins secure the scissor legs for inspection and maintenance on larger models
- Quality powder coated finish provides exceptional durability and corrosion resistance





Model	Load Cap.	Load Cap. Platform Height		Platform I	Dimensions	Handle	Pedal Strokes	Wt.	
No.	lbs.	Lowered"	Raised"	Width"	Length"	Height"	To Max	lbs.	
MJ518	330	8 5/8	29	17 3/4	27 1/2	37 3/8	28	99	
MJ519	660	11 1/4	34 5/8	19 3/4	32	39	27	170	
MJ520*	770	14	51 1/4	19 3/4	35 3/4	38 3/8	53	230	
MJ521	1100	11 1/4	345/8	19 3/4	32	39	27	179	
MJ522	1100	11 1/4	36	31 7/8	63	39	55	340	
MJ523	1650	16 1/2	35 3/8	20 1/8	39 3/8	39 3/8	45	275	
MJ524	2200	15	39	20 1/8	40	38 5/8	82	269	
MJ525	2200	11 3/4	53 1/2	29 1/2	80 1/8	39 3/8	200	770	
MJ526*	1760	17 1/2	59 1/8	24	48	40	97	430	

^{*}Double scissors

HYDRAULIC WORK TABLES

- All-welded construction
- Foot operated lifts are ideal for wide variety of shop functions (lifting dies, transporting heavy parts and positioning materials)
- Hand operated lever lowers the table level and controls the rate of descent
- · Telescoping posts for stability and support
- Tops and bases are 3/16" thick steel
- · Floor lock ensures table remains in place when loaded

AIR PALLET PAL LEVEL LOADERS

- Designed for use where pallet loads vary and are changed frequently
- 43 5/8" diameter rolled angle ring riding on low friction bearings and guided by center shaft
- Permanent spring combines with air bag to provide linear response
- Equipped with fork pockets for easy relocation
- Lowered height of 9 1/2", raised height of 30 1/2"
- Base frame dimensions: 48" L x 36" W, including fork truck pockets
- Capacity: 400 to 4500 lbs.
- Weight: 460 lbs.

Model No. LT471





Model	Table	Height	Table D	ime	nsions	Cap.	Wt.
No.	Lowered"	Raised"	Length"	х	Width"	lbs.	lbs.
MA433	28 1/2	46	16	Х	16	200	54
MA434	30 1/2	47 1/2	18	χ	18	500	122
MA435	30 1/2	47 1/2	18	Х	36	1000	268
MA442	30 1/2	47 1/2	36	χ	24	2000	225
MA443	30 1/2	47 1/2	48	χ	32	2000	350

Other dimensions and capacities available







LIFT TABLES & SKID LIFTS

DANDY LIFTTM

 Dandy Lift[™] offers the ideal solution to reliable, economic lifting over years of service


Pivot points have hardened pins in lifetime lubricated bearings
 Simple grouped controls make tables easy to operate

 Hard chrome-plated pistons and rods resist rust and corrosion for dependability and long life

Honed heavy-walled cylinders improve both seal performance and durability

LOW PROFILE DANDY LIFT™

- Ideal for use in factories, warehouses and repair shops
- Fully lowered height of only 3 1/5"
- Platform fits easily under most skids and wire baskets
- Comes with two rigid and two swivel rubber casters
- · Floor lock brake is standard





Model	Plat	form	Platform Dim.		0v	Overall Dim.		Foot pedal	Cap.	Wt.	
No.	Lowered"	Raised"	L"	x	W"	L"	x	W"	Strokes to Max.	lbs.	lbs.
MA431	8 3/10	29	28	Х	17 7/10	37 7/10	Х	17 7/10	14	330	82
MA432	9 1/2	31 1/2	31 1/2	Х	19 7/10	38 1/5	Х	19 7/10	20	550	115
MA421	13 3/5	49 4/5	35 4/5	Х	23 3/5	42 1/10	Х	23 3/5	45	770	229
MA422	11 4/5	36 3/5	35 4/5	Х	23 3/5	42 1/10	Х	23 3/5	45	1100	194
MA423	13	40 1/5	39 2/5	Х	23 3/5	45 9/10	Х	23 3/5	56	1760	275
MA464*	3 1/5	29 1/2	37 1/10	Х	19 7/10	55 2/5	Х	19 7/10	15	1100	174


^{*} Low profile

SCISSOR LIFT PALLET TRUCK

- Frame material : Steel
- · Lifting capacity: 2500 lbs.
- Fork width: 7'
- · Raised height: 31.5"
- Lowered height: 3.5"Steel load backrest
- Leak-proof pump w/overload protect
- Automatic brake system
- 3-position finger tip control handle
- Dual cylinder w/chain pull design
- 3" nylon load rollers
- 4" x 2" phenolic swivel casters

BATTERY POWERED LIFT

- Fully raised in 6 seconds
- Approx. 50 max. load lifts on one battery charge
- · Heavy duty 12 V, 125 Ah industrial strength battery
- 10 A charger with transformer, circuit breaker and overload protection
- Can be plugged into any standard 110 V outlet





OBILE

SKID LIFTS

- · Allows entry into different skids and baskets
- Lightweight design is easy to manoeuvre with pallet truck style steering configuration
- Strong and reliable cylinder
- Quick-lift mechanism on manual lifts allows loads under 400 lbs. to be raised with 24 strokes, heavier loads require 72 strokes
- Self-contained battery powered power pack (electric models) eliminates power source or power cord problems
- Built-in automatic battery charger and charge indicator (electric models)
- Capacity: 3000 lbs.

24" load centre

charger and clear view of load

8" polyurethane load wheels

and 3" polyurethane load roller



ELECTRI	LIFIS		_	
Model	Fork D	ime	ensions	Wt.
No.	Ľ"	X	W"	lbs.
MH796	48	Х	20 1/2	430
MH797	48	χ	27	440

· Raised bulkhead design provides greater backrest

• Lowered height: 3 1/4", raised height: 31 1/2"

surface, ergonomic location for automatic battery



MANUAL LIFTS

Model	Fork Dimensions	Wt.	
No.	L" x W"	lbs.	
MH748	48 x 20 1/2	330	
MH749	48 x 27	340	

WAREHOUSE TRUCKS & CARTS

FRAME SHEET/PANEL TRUCKS

- · All-welded truck is ideal for handling long, flat, awkward loads
- · Available with open or closed base
- · Four bolted-on 5" non-marking rubber swivel casters
- Capacity: 1200 lbs.
- · Durable Kleton blue enamel finish







Model	Base			Wt.			
No.	Type	W"	x	L"	X	H"	lbs.
MD216	Open	24	Х	36	Х	55	50
ML063	Closed	24	Х	36	Х	5	60
MD217	0pen	30	Х	42	Х	55	60
ML064	Closed	30	Х	42	Х	55	75
MD218	Open	36	Х	72	Х	55	85
ML065	Closed	36	Х	72	Х	55	110

REPLACEMENT CASTERS

MI 337

5" Swivel Non-Marking Rubber Caster

DRYWALL CARTS

- · All-welded multi-purpose cart is ideal for transporting drywall, wood or metal sheets
- 1 1/4" tubular rail handle and thick 11-gauge steel platform
- Two rigid and two swivel 8" bolted-on casters
- Deck dimensions: 15" W x 44" L x 14" H
- Overall dimensions: 24" W x 44" L x 44" H
- Durable Kleton blue enamel finish







Model No.	Caster Type	Deck Angle°	Cap. Ibs.	Wt. Ibs.
ML139	8" Mold-On Rubber	80	2000	115
MD214	8" Polyurethane	80	3500	110

LUMBER CARTS

- All-welded cart is ideal for transporting long and bulky items
- Welded 14-gauge 12" x 38" steel shelf
- Grey rubber bumpers protect
- walls and equipment Two rigid and two swivel
- bolted-on casters · Capacity: 1200 lbs.
- · Durable Kleton blue enamel finish







Model		De	ck D	im.		Shelf	Overall Dim.			Dim		Caster	Wt.
No.	W"	X	Ľ"	X	H"	Height"	W"	x	L"	x	Н"	Type	lbs
MB729	24	Х	36	Х	8	34	26	Х	39	Х	42	5" Rubber	80
ML140	24	Х	36	Χ	10	36	26	Х	39	Х	45	6" Rubber	100

HIGH END PLATFORM TRUCKS

- · Tilt design allows truck to turn within its own radius
- 11-gauge steel deck is only 10" off the ground for easy loading
- Removable end racks constructed of 1 1/4" round steel tube
- Two 8" x 2" bolted-on rigid caster and four 5" swivel casters
- Capacity: 1500 lbs.
- Durable Kleton blue enamel finish

MK970





Model	0v	erall	Wt.				
No.	W"	X	L"	X	Н"	lbs.	
MK970	18	Х	48	Х	72	115	
MK971	18	χ	60	Х	72	125	



- LUMBER MOVER TRUCKS · All-welded, ready to use
- Constructed from 1 1/4" round tubing and an 11-gauge deck
- Ideal for transporting large sheets and long parts
- Uprights extend 21" and 33" above deck
- Deck is 12" off the floor
- 8" clear space between tubes
- Two rigid and two swivel 8" casters
- · Durable Kleton blue enamel finish







Model	C)veral	l Dimer	sions		Caster	Cap.	Wt.
No.	W"	x	L"	x	H"	Type	lbs.	lbs.
ML360	30	Х	48	Х	45	Mold-On Rubber	2000	160
ML361	30	Х	48	Х	45	Polyurethane	2500	175
ML362	30	Х	60	Х	45	Mold-On Rubber	2000	160
ML363	30	Х	60	Χ	45	Polyurethane	2500	175

SINGLE LEVEL RAILS HEAVY-DUTY PANEL MOVER TRUCKS

- All-welded truck ideal for transporting large sheets and long parts
- Construction from 1 1/4" round tubing and reinforced 11-gauge deck
- Uprights extend 33" above deck • Deck is 12" off the floor
- Overall height is 45"
- 8" clear space between tubes
- · Two rigid and two swivel 8" casters
- Durable Kleton blue enamel finish







Model	Overall Dimensions					Caster	Capacity	Wt.
No.	W"	X	L"	x	H"	Туре	lbs.	lbs.
ML549	30	Х	48	Х	45	8" Mold-On Rubber	2000	139
ML550	30	Х	48	Х	45	8" Polyurethane	2500	139
ML551	30	Х	60	Х	45	8" Mold-On Rubber	2000	161
ML552	30	χ	60	Х	45	8" Polyurethane	2500	161



CUSTOMISE IT TO YOUR SPECIFICATIONS. **SEE PAGE B71 FOR DETAILS**

COMMERCIAL DUTY SHELF CARTS

HEAVY-DUTY LOW PROFILE SHOP CARTS

- · All-welded cart with low shelf means less distance to lift heavy objects
- Two 14-gauge steel shelves with a 1 1/2" lip down
- 1 1/4" diameter tubular steel handle
- · Two rigid and two swivel bolted-on casters
- · Durable Kleton blue enamel finish



5" RUBBER CASTERS

- · Non-marking casters are quiet rolling and ideal for both institutional and industrial applications
- · Casters are resistant to wet and corrosive chemical conditions
- Capacity: 1200 lbs. evenly distributed

Model	Shelf	Dime	nsions	Clearance	Top Shelf		0.	A. Dim			Wt.
No.	W"	X	L"	Between Shelves"	Height"	W"	X	L"	x	Н"	lbs.
MB421	18	Х	30	16	26	18	Х	34	Х	40	90
MB425	24	Х	36	16	26	24	Χ	40	Х	40	110
MB429	24	Х	48	16	26	24	Χ	52	Х	40	125
ML097	24	Х	60	16	26	24	Х	64	Х	40	155
ML098	30	Х	48	16	26	30	Χ	52	Х	40	155
MB434	30	Х	60	16	26	30	Χ	64	Х	40	165
ML099	30	Х	72	16	26	30	Χ	76	Х	40	175

6" HI-TEMP NYLON OR POLYURETHANE CASTERS

- · Solid black hi-temp nylon casters handle heavy loads easily
- · Solid polyurethane casters are non-marking and are highly resistant to wear
- Best choice in uneven floor applications
- Capacity: 2400 lbs. evenly distributed

6" Nylon Model No.	6" Polyurethane Model No.	Shelf Dim. W" x L"	Clearance Between Shelves"	Top Shelf Height"	0.A. Dim. W" x L" x H"	Wt. Ibs
MB422	ML103	18 x 30	16	27	18 x 34 x 41	100
MB426	ML104	24 x 36	16	27	24 x 40 x 41	130
MB430	ML105	24 x 48	16	27	24 x 52 x 41	145
ML100	ML106	24 x 60	16	27	24 x 64 x 41	155
ML101	ML107	30 x 48	16	27	30 x 52 x 41	155
MB435	ML108	30 x 60	16	27	30 x 64 x 41	165
ML102	ML109	30 x 72	16	27	30 x 76 x 41	175

STOCK PICKING CARTS

- · All-welded design for durability and long life
- Pick and transport stock without the need for a separate ladder

· Slip-resistant steps and positive locking engagement for safety

Step rise: 9 1/2"

- Three 14-gauge steel shelves with 1 1/2" lip, configured up
- Clearance between shelves: 12"
- Two rigid and two swivel bolted-on 5" non-marking rubber casters
- · Capacity: 1200 lbs. evenly distributed
- · Durable Kleton blue enamel finish







Model		ihel Dim		Number of		Ste _l Dim				veral nensi			Wt.
No.	W"	x	D"	Steps	W"	X	D"	W"	X	D"	X	Н"	lbs.
MD441	24	Х	36	3	22	Х	4	24	Х	52	Х	61	135
MB507	24	Х	48	3	22	Х	4	24	Х	64	Х	61	140
MD442	24	Х	36	5	22	Х	4	24	Х	52	Х	78	145
MB508	24	x	48	5	22	x	4	24	X	64	x	78	150



SHELF/PLATFORM TRUCKS

- 2-in-1 shelf truck features removable top shelf and post assembly - converts into a platform truck when removed
- Standard features include: two front corner non-marking bumpers, four 5" non-marking rubber casters (two rigid and two swivel), two crossbars on push handle, all-welded heavy gauge steel assembly
- Shelf dimensions: 24" W x 36" L
- Top shelf capacity: 500 lbs. evenly distributed
- Bottom shelf capacity: 800 lbs. evenly distributed
- Durable Kleton blue enamel finish

Model		0	.A. Di	m.		Top Shelf	Wt.
No.	W"	x	L"	X	H"	Н"	lbs.
MB391	26	Х	38	Х	40	32	105





DEEP-LIPPED SERVICE CARTS

- All-welded design, ready-to-use
- Deep shelf lips for retention
- Two 14-gauge steel shelves welded to 1 1/2" x 1 1/2" x 1/8" steel posts
- 1" diameter tubular ergonomic handle
- Two rigid and two swivel
- 5" non-marking rubber casters
- Overall dimensions: 24" W x 42" D x 47" H
- Capacity: 1200 lbs. evenly distributed
- Durable Kleton blue enamel finish





Model No.	Shelf Dim. W" x D"		Shelf Lip Depth	Clearance Between Shelves	Wt. Ibs.	
MN393	24	Х	36	Top 6"/Bottom 1 1/2"	22 1/2	85
MN394	24	χ	36	Top 12"/Bottom 1 1/2"	16	90
MN395	24	v	36	Ton 6"/Rottom 6"	18	90

MOBILE SERVICE CARTS

- · All-welded design, ready-to-use
- Louvered panels for small parts bins and lockable drawer for supplies
- Two 14-gauge steel shelves welded to 1 1/2" x 1 1/2" x 1/8" steel posts
- 1" diameter tubular handle
- Two rigid and two swivel with brake bolted-on 5" non-marking rubber casters
- Overall dimensions: 24" W x 40" L x 57" H
- Capacity: 1200 lbs. evenly distributed
- Durable Kleton blue enamel finish





ET GA		
	Clearance	Wt.
	Between Shelves	lbs.

No. Description 24 x 36 Top Lip Down /Bottom Lip Up

ELEVATED PLATFORM TRUCKS All-welded steel construction, ready-to-use

Shelf Dim.

- 11-gauge steel deck with 2" square tube frames
- 1 1/4" round tube handle extends 14" above deck
- Removable handle

Mode

Durable Kleton blue enamel finish





Nodel	Platforr	n Dim	ensions	Deck	Wheel	Capacity	Wt.	
lo.	W"	X	L"	Height	Туре	lbs.	lbs.	
ΛN413	24	Х	48	28	8" Hi-Temp Nylon	2000	140	
AN414	30	Χ	60	28	8" Hi-Temp Nylon	2000	172	
AN415	24	Х	48	28	8" Mold-On Rubber	1800	140	
AN416	30	Х	60	28	8" Mold-On Rubber	1800	172	
ΛN417	24	Х	48	31	10" Pneumatic	1000	140	
AN418	30	х	60	31	10" Pneumatic	1000	172	

COMMERCIAL DUTY SHELF CARTS

KNOCKED-DOWN SHELF CARTS

- 16-gauge steel shelves with 2 1/2" high lip
- 1 1/2" x 1 1/2" x 12-gauge formed steel posts
- 1 1/4" diameter tubular steel handle
- Top and middle shelves can be installed lip up or down
- · Two rigid and two swivel bolted-on casters
- Easy-to-assemble shipped knocked-down design
- Capacity: 900 lbs. evenly distributed
- · Durable Kleton blue powder coat finish





2-SHELF UTILITY CARTS

Model No.	Shelf Dim. W" x D"	Shelf Clearance"	Post Height"	Overall Height"	Wt. Ibs.	
5" BLUE EI	LASTIC RUBBE	R CASTERS				
MB492	18 x 30	25	30	36	43	
MB493	24 x 36	25	30	36	54	
MB494	24 x 48	25	30	36	69	
5" POLYO	LEFIN CASTER	S				
MB482	18 x 30	25	30	36	42	
MB483	24 x 36	25	30	36	53	
MB484	24 x 48	25	30	36	68	
8" PNEUN	ATIC CASTER	S				
MB488	24 x 36	25	30	40	60	
MB489	24 x 48	25	30	40	75	

4-SHELF UTILITY CARTS

Model	Shelf Dim.	Shelf	Post	Overall	Wt.	
No.	W" x D"	Clearance"	Height"	Height"	lbs.	
5" BLUE E	LASTIC RUBBE	R CASTERS				
ML145	18 x 30	10	42	48	66	
ML146	24 x 36	10	42	48	85	
ML147	24 x 48	10	42	48	115	
ML148	18 x 30	15	55	61	68	
ML149	24 x 36	15	55	61	87	
ML150	24 x 48	15	55	61	117	
5" POLYO	LEFIN CASTER	S				
MN148	18 x 30	10	42	48	65	
MN149	24 x 36	10	42	48	84	
MN150	24 x 48	10	42	48	114	
MN151	18 x 30	15	55	61	67	
MN152	24 x 36	15	55	61	86	
MN153	24 x 48	15	55	61	116	
8" PNEUM	NATIC CASTERS	5				
MN154	24 x 36	10	42	52	90	
MN155	24 x 48	10	42	52	120	
MN156	24 x 36	15	55	65	92	
MN157	24 x 48	15	55	65	122	

ERGONOMIC SHELF CARTS

- · All-welded 16-gauge construction
- All-welded ergonomic handle placed at a comfortable working height
- Two rigid and two swivel 5" casters
- Capacity: 800 lbs. evenly distributed Durable Kleton blue enamel finish

15.4770	-		м, я
1807.01	1000	100	wa
TROUTE	100	110 28	oa
111/03/15	-0.700	1 1 1 1 1 1	



Model	Number of	ıber of Caster Overall Di			im	ensi	ons
No.	Shelves	Туре	W"	x [)"	X	H"
ML561	2	Blue Rubber	20	x 3	2	Х	37
MN056	2	Blue Rubber	26	x 3	8	Х	37
ML562	3	Blue Rubber	20	x 3	2	Х	37
MN055	3	Blue Rubber	26	x 3	8	Х	37
ML563	2	Polyolefin	20	x 3	2	Х	37
ML883	2	Polyolefin	26	x 3	8	Х	37
ML564	3	Polyolefin	20	x 3	2	Х	37
ML884	3	Polyolefin	26	x 3	8	χ	37



CUSTOMISE IT TO YOUR SPECIFICATIONS. **SEE PAGE B71 FOR DETAILS**





3-SHELF UTILITY CARTS

Model No.	Shelf Dim. W" x D"	Shelf Clearance"	Post Height"	Overall Height"	Wt. Ibs.
5" BLUE E	LASTIC RUBBE	R CASTERS			
MB495	18 x 30	11	30	36	54
MB496	24 x 36	11	30	36	70
MB497	24 x 48	11	30	36	93
ML142	18 x 30	17	42	48	56
ML143	24 x 36	17	42	48	72
ML144	24 x 48	17	42	48	95
5" POLYC	LEFIN CASTER	S			
MB485	18 x 30	11	30	36	53
MB486	24 x 36	11	30	36	69
MB487	24 x 48	11	30	36	92
MN143	18 x 30	17	42	48	55
MN144	24 x 36	17	42	48	71
MN145	24 x 48	17	42	48	94
8" PNEU	MATIC CASTER	S			
MB490	24 x 36	11	30	40	77
MB491	24 X 48	11	30	40	100
MN146	24 x 36	17	42	52	79
MN147	24 X 48	17	42	52	102

5-SHELF UTILITY CARTS

Model No.	Shelf Dim. W" x D"	Shelf Clearance"	Post Height"	Overall Height"	Wt. Ibs.	
5" BLUE EL	ASTIC RUBBE	R CASTERS				
ML151	18 x 30	10	55	61	80	_
ML152	24 x 36	10	55	61	100	
ML153	24 x 48	10	55	61	135	
5" POLYOL	EFIN CASTERS	5				
MN158	18 x 30	10	55	61	79	
MN159	24 x 36	10	55	61	99	
MN160	24 x 48	10	55	61	134	
8" PNEUM	ATIC CASTERS	5				
MN161	24 x 36	10	55	65	105	
MN162	24 x 48	10	55	65	140	



HEAVY-DUTY SHELF CARTS

HEAVY-DUTY SHELF CARTS

- · All-welded design ready to use
- Cart constructed from 14-gauge steel shelves welded to 1 1/2" x 1 1/2" x 1/8" steel angle posts
- Versatile for all material transport
- · 1" diameter tubular steel handle
- Shelves are available with a 1 1/2" lip configured up or down
- Two rigid and two swivel 5" non-marking casters
- · Capacity: 1200 lbs. evenly distributed
- Durable Kleton blue enamel finish









OVERALL HEIGHT: 36"

Lip Up Lip Down		Shelf Dimensions			No.	Clearance	Handle	Overall Dimensions	Wt.
Model No.	Model No.	W"	X	D"	Shelves	Between Shelves"	Height"	W" x D" x H"	lbs.
MB445	MB444	18	Х	30	2	27	36	18 x 33 x 36	60
MB447	MB446	24	Х	36	2	27	36	24 x 39 x 36	65
MB449	MB448	24	Х	48	2	27	36	24 x 51 x 36	100
MB456	MB455	18	Х	30	3	12	36	18 x 33 x 36	75
MB459	MB458	24	Х	36	3	12	36	24 x 39 x 36	85
MB461	MB460	24	Х	48	3	12	36	24 x 51 x 36	110

OVERALL HEIGHT: 48"

Lip Up Model No.	Lip Down Model No.	Shelf W"	Dimer x	nsions D"	No. Shelves	Clearance Between Shelves"	Handle Height"	Overall Dimensions W" x D" x H"	Wt. Ibs.
ML084	ML083	18	Х	30	3	18	42	18 x 33 x 48	80
ML086	ML085	24	Х	36	3	18	42	24 x 39 x 48	90
ML088	ML087	24	Х	48	3	18	42	24 x 51 x 48	115
ML090	ML089	18	Х	30	4	12	42	18 x 33 x 48	110
ML092	ML091	24	Х	36	4	12	42	24 x 39 x 48	135
ML094	ML093	24	Х	48	4	12	42	24 x 51 x 48	160

OVERALL HEIGHT: 61"

	Lip Down	Shelf	Dimer	sions	No. Shelves	Clearance Between Shelves"	Handle	Overall Dimensions	Wt. Ibs.
	Model No.	W"	X	D"			Height"	W" x D" x H"	
MB468	MB467	18	Х	30	4	16	42	18 x 33 x 61	115
MB470	MB469	24	Χ	36	4	16	42	24 x 39 x 61	140
MB472	MB471	24	Χ	48	4	16	42	24 x 51 x 61	165
MB474	MB473	18	Х	30	5	11	42	18 x 33 x 61	125
MB476	MB475	24	Χ	36	5	11	42	24 x 39 x 61	155
MB478	MB477	24	Х	48	5	11	42	24 x 51 x 61	184



HEAVY-DUTY SHELF CARTS WITH DRAWER

- · All-welded design ready to use
- Carts constructed from 14-gauge steel shelves welded to 1 1/2" x 1 1/2" x 1/8" steel angle posts
- 1" diameter tubular steel handle
- Drawer dimensions: 15 1/4" W x 20" D x 6" H, 100-lb. capacity
- Available with two or three shelves with 1 1/2" lip configured up
- Two rigid and two swivel bolted-on 5" non-marking casters
- · Capacity: 1200 lbs. evenly distributed
- · Durable Kleton blue enamel finish





Model	Shelf I			Number of	Clearance	Drawer to Shelf	Handle		Overa				Wt.
No.	W"	Х	D"	Shelves	Between Shelves"	Clearance"	Height"	W"	X	D"	X	н"	lbs.
MH255	24	χ	36	2	27	18	36	24	Х	39	Х	36	75
MH256	24	Χ	36	3	12	3	36	24	Х	39	Х	36	95




ORDER PICKING CARTS

- · All-welded design for durability and long life
- · Picking list holder eliminates the need to handle loose papers
- 14-gauge steel shelves with 1 1/2" lip, configured up
- · Two rigid and two swivel bolted 5" non-marking rubber casters
- Capacity: 1200 lbs. evenly distributed
- · Durable Kleton blue enamel finish











CUSTOMISE IT TO YOUR SPECIFICATIONS. **SEE PAGE B71 FOR DETAILS**

SERVICE & UTILITY CARTS

PLASTIC FLAT SHELF UTILITY SERVICE CART

- Durable structural foam construction will not dent, rust or bend
- Non-marking 4" casters
- · Flat top shelf makes loading and unloading of heavy boxes easy
- Overall dimensions: 25 1/2" W x 40 1/2" L x 32 1/2" H
- Capacity: 500 lbs.

Model No. ML620





PLASTIC UTILITY SERVICE CARTS

- Durable structural foam construction will not dent, rust or bend
- Non-marking 4" casters
- Capacity: 500 lbs





Model Overall Dimensions							
No.	W"	X	Ľ"	X	H"		
ML618	17 1/2	Х	34 1/2	Х	32 1/2		
ML619	25 1/2	Х	40 1/2	Х	32 1/2		

LIGHT-DUTY UTILITY CARTS

- · Durable plastic construction
- Comes with middle shelf and two convenient handles
- Shelves are flat with retaining beaded edges
- · 4" swivel non-marking casters
- Platinum
- Assists in complying with HACCP guidelines



Model	Shelf Dimensions		Capacity	Wt.			
No.	W"	X	L"	X	H"	lbs.	lbs.
MH223	19	Х	34	χ	38	200	30
CART W	ENCL	.OS	ED I	END	PANE	LS	
MH829	18	Х	31	Х	37 1/2	300	37

MH223

STANDARD/MEDIUM DUTY STAINLESS STEEL CARTS

- · Durable chassis frame with protective bumpers on legs and handle
- Ideal for constant usage with light to moderate loads
- 1" edge on three sides of top and middle shelves
- All edges down on bottom shelf
- All rubber swivel casters standard





Model	Shelf Di	mer	sions	No. of	f Overall Dimensions					Caster	Cap.	Wt.
No.	W"	x	L"	Shelves	W"	X	L"	X	H"	Dim."	lbs.	lbs.
MI812	15 1/2	Х	24	3	16 1/4	χ	27 1/2	Х	32 1/8	3 1/2	300	29
MI813	18	Χ	27	3	18 3/8	Х	30 3/4	Х	33	3 1/2	300	32
MI816	15 1/2	Χ	24	3	16 3/4	Х	27 5/8	Х	32 1/8	4	500	39
MI817	18	Х	27	3	19	Х	31	Х	32 1/8	4	500	42
MI818	21	Х	35	3	22 3/8	Х	39 1/4	χ	37 1/4	5	500	68

TRADES CARTS

- · Use as mobile workbench
- Sized to hold large tools and supplies yet fits in tight spaces
- Four compartmentalised parts box and two versatile storage bins
- Mounting bracket to serve as an electrical cord wrap and convenient handle bin to keep small tools/parts
- Constructed of black plastic for lightness and durability
- 5" casters (two with brakes)
- Also available with a fully enclosed, lockable storage compartment 19 1/4" W x 38" L x 33 3/8" H
- Capacity: 180 lbs. (top shelf), 150 lbs. (bottom shelf)
- · Assembly required

Model No. MK744

Trades Cart Wt.: 50 lbs.

Model No. MK745

Trades Cart w/Lockable Cabinet Wt.: 68 lbs



MK744



FLAT SHELF UTILITY CARTS

- Ergonomic handle design improves control and worker safety
- Flat design makes loading and unloading of heavy boxes and parts easier
- Easy to reach tool/accessory hooks and storage area enhances productivity and organization
- Top shelf perimeter channel retains small items
- Constructed from sturdy structural foam that will not rust, dent, chip nor splinter
- Two rigid and two swivel 5" non-marking TPR casters
- Assembly required





Model No.			Dimensio	ns	Capacity	Wt.	
Black	Beige	W" x	L"	X	H"	lbs.	lbs.
ML456	ML457	17 1/4 x	38 1/2	Х	38 1/4	500	33
ML458	ML459	25 7/8 x	43 7/8	Х	33 1/4	500	42
ML460	ML461	25 1/4 x	54	Х	38	750	52

Note: Other sizes and accessories available

HEAVY-DUTY UTILITY CARTS

- · Ergonomic handle design improves control and worker safety
- Easy to reach tool/accessory hooks and storage area enhances productivity and organization
- 2 3/4" deep top shelf securely holds contents
- Constructed from sturdy structural foam that will not rust, dent, chip nor splinter
- Two rigid and two swivel casters
- · Assembly required





Mode	el No.	Caster	Dimensions					Capacity	Wt.
Black	Beige	Type	W"	X	L"	X	H"	lbs.	lbs.
ML448	ML449	5" Non-Marking TPR	17 7/8	Х	39	Х	33 1/4	500	31
ML450	ML451	5" Non-Marking TPR	25 7/8	Χ	45 1/4	Χ	33 1/4	500	44
ML452	-	8" Pneumatic	25 7/8	Χ	45 1/4	Χ	37 1/8	500	66
ML453	-	5" Non-Marking TPR	26	Х	55	Χ	33 1/4	750	52
ML455	-	8" Pneumatic	26	Χ	55	Χ	33 1/4	750	74

Note: Other sizes and accessories available

WIRE MESH STOCK CARTS

WIRE MESH UTILITY CARTS - Rugged all-welded steel construction ready to use

- Designed for efficient loading/unloading and transportation of merchandise
- 14-gauge steel shelves, 1 1/2" lip up
- Frame constructed from 1 1/2" angle iron and 2" x 2" wire mesh

- Includes: Two rigid and two swivel
 - 5" or 6" bolted-on casters
- Capacity: 1200-2400 lbs. evenly distributed
- · Durable Kleton blue enamel finish

5" Non-Marking Rubber 1200-lb. Cap. Model No.	6" Polyurethane 2400-lb. Cap. Model No.	Base W" x L"	Inside Wall Height"	Handle Height"	Clearance Between Shelves"	Overall Dimensions W" x L" x H"	Wt. Ibs.
TWO-SIDED, TWO SHEL	VES						
ML162	ML168	24 x 36	55	42	26	24 x 39 x 63	95
ML163	ML169	24 x 48	55	42	26	24 x 51 x 63	112
ML164	ML170	24 x 60	55	42	26	24 x 63 x 63	127
ML165	ML171	30 x 48	55	42	26	30 x 51 x 63	129
ML166	ML172	30 x 60	55	42	26	30 x 63 x 63	144
ML167	ML173	30 x 72	55	42	26	30 x 75 x 63	167
TWO-SIDED, THREE SH	ELVES						
ML174	ML180	24 x 36	55	42	16 1/2	24 x 39 x 63	120
ML175	ML181	24 x 48	55	42	16 1/2	24 x 51 x 63	137
ML176	ML182	24 x 60	55	42	16 1/2	24 x 63 x 63	152
ML177	ML183	30 x 48	55	42	16 1/2	30 x 51 x 63	154
ML178	ML184	30 x 60	55	42	16 1/2	30 x 63 x 63	169
ML179	ML185	30 x 72	55	42	16 1/2	30 x 75 x 63	192
THREE-SIDED, ONE SHE	LF						
ML220*	ML190*	24 x 36	55	42	-	24 x 39 x 63	102
ML221*	ML191*	24 x 48	55	42	-	24 x 51 x 63	110
ML222*	ML192*	24 x 60	55	42	-	24 x 63 x 63	120
ML223*	ML193*	30 x 48	55	42	-	30 x 51 x 63	135
ML224*	ML194*	30 x 60	55	42	-	30 x 63 x 63	145
ML225*	ML195*	30 x 72	55	42	-	30 x 75 x 63	155
THREE-SIDED, TWO SH	ELVES						
ML196	ML202	24 x 36	55	42	26	24 x 39 x 63	127
ML197	ML203	24 x 48	55	42	26	24 x 51 x 63	142
ML198	ML204	24 x 60	55	42	26	24 x 63 x 63	159
ML199	ML205	30 x 48	55	42	26	30 x 51 x 63	182
ML200	ML206	30 x 60	55	42	26	30 x 63 x 63	192
ML201	ML207	30 x 72	55	42	26	30 x 75 x 63	211
THREE-SIDED, THREE SI	HELVES						
ML208	ML214	24 x 36	55	42	16 1/2	24 x 39 x 63	152
ML209	ML215	24 x 48	55	42	16 1/2	24 x 51 x 63	174
ML210	ML216	24 x 60	55	42	16 1/2	24 x 63 x 63	198
ML211	ML217	30 x 48	55	42	16 1/2	30 x 51 x 63	229
ML212	ML218	30 x 60	55	42	16 1/2	30 x 63 x 63	239
ML213	ML219	30 x 72	55	42	16 1/2	30 x 75 x 63	267
* Base shelf only							









SECURITY TRUCKS

- · Rugged all-welded steel construction, ready to use
- Designed for efficient loading/unloading and transportation of merchandise
 14-gauge steel shelves, 1 1/2" lip up
- Frame constructed from 1 1/2" angle iron and 2" x 2" wire mesh
- Includes: Two rigid and two swivel 5" or 6" bolted-on casters
- Comes with hasp for padlock
 Capacity: 1200-2400 lbs. evenly distributed
- Durable Kleton blue enamel finish

5" Non-Marking Rubber 1200-lb. Cap. Model No.	6" Polyurethane 2400-lb. Cap. Model No.	Base W" x L"	Inside Wall Height"	Handle Height"	Clearance Between Shelves"	Overall Dimensions W" x L" x H"	Wt. Ibs.
TWO SHELVES							
ML238	ML244	24 x 36	55	42	25	26 x 39 x 62 1/2	157
ML239	ML245	24 x 48	55	42	25	26 x 51 x 62 1/2	172
ML241	ML247	30 x 48	55	42	25	32 x 51 x 621/2	212
ML242	ML248	30 x 60	55	42	25	32 x 63 x 62 1/2	222
ML243	ML249	30 x 72	55	42	25	32 x 75 x 62 1/2	241
THREE SHELVES							
ML250	ML256	24 x 36	55	42	16	26 x 39 x 62 1/2	182
ML251	ML257	24 x 48	55	42	16	26 x 51 x 62 1/2	204
ML253	ML259	30 x 48	55	42	16	32 x 51 x 621/2	259
ML254	ML260	30 x 60	55	42	16	32 x 63 x 62 1/2	269
ML255	ML261	30 x 72	55	42	16	32 x 75 x 621/2	297

BOX TRUCKS

- Rugged all-welded steel construction, ready to use
- Contain and transport small bulk parts or materials in your plant or warehouse
- Frame constructed from 1 1/2" angle iron construction and 2" x 2" wire mesh

Model	Base	Inside Wall	Handle	Overall Dim.Wt.					
No.	W" x L"	Height"	Height"	W"	X	L"	X	H"	lbs.
MB672	24 x 36	24	30	24	Х	39	Х	31 1/2	62
ML186	24 x 48	24	30	24	Х	51	Х	31 1/2	75
ML187	24 x 60	24	30	24	Х	63	Х	31 1/2	85

- Includes: Two rigid and two swivel 5"
- non-marking bolted-on rubber casters Capacity: 1200 lbs. evenly distributed
- · Durable Kleton blue enamel finish

Model	Base	Inside Wall	Handle	0	ve	ral	I D	im.	Wt.
No.	W" x L"	Height"	Height"	W"	X	L"	X	H"	lbs.
ML188	30 x 48	24	30	30	Х	51	Х	31 1/2	86
MB680	30 x 60	24	30	30	Х	63	Х	31 1/2	95
ML189	30 x 72	24	30	30	X	75	Х	31 1/2	107







ML254





CASTERS

GENERAL USE CASTERS

POLYOLEFIN CASTERS

- · Rolls easily and quietly on all floors
- · Lightweight and economical
- · Non-marking, easy to maintain, steam cleanable
- · High impact strength
- Superior resistance to most oils, chemicals, grease and acids

Applications:

For food service equipment, mobile warehouse equipment, factories and abusive environments.

Plate dimensions: 2 5/8" x 3 3/4" **Bolt hole centres:** 1 3/4" x 2 7/8" **Bolt hole dimension:** 5/16"



Model No.	Wheel Dia."	Caster Type	Capacity lbs.	Tread Width"	Overall Height"
ML391	3	Swivel	250	1 1/4	4 1/2
ML392	3	Rigid	250	1 1/4	4 1/2
ML393	4	Swivel	250	1 1/4	5 1/4
ML394	4	Rigid	250	1 1/4	5 1/4
ML395	5	Swivel	250	1 1/4	6 1/8
ML396	5	Rigid	250	1 1/4	6 1/8

POLYURETHANE CASTERS

- Smooth rolling, low noise operation
- Non-marking, cut and tear resistant
- · Die cast aluminum core with brown polyurethane tread
- Resistant to most chemicals, moisture friendly
- Double ball raceway
- Annular ball bearing
- Brake type: Total locking

Applications:

Food service equipment, factory use, mobile warehouse equipment.



Plate dimensions:	Bolt hole centres:	Bolt hole dimension:
3 = 2 5/8" x 3 3/4"	3 = 1 3/4" x 2 3/4"	3 = 5/16"
4 = 3 1/8" x 4 1/8"	4 = 2 3/8" x 3 1/16"	4 = 5/16"
4 HD = 4" x 4 1/2"	4 HD = 3 1/4" x 2 3/4"	4 HD = 3/8"
5 = 4" x 4 1/2"	5 = 3 1/4" x 2 3/4"	5 = 3/8"
6 = 4" x 4 1/2"	6 = 3 1/4" x 2 3/4"	6 = 3/8"
8 = 4" x 4 1/2"	8 = 3 1/4" x 2 3/4"	8 = 3/8"


Model No.	Wheel Dia."	Caster type	Capacity lbs.	Thread Width"	Overall Height"
ML044	3	Swivel	230	1 1/4	4 1/4
ML043	3	Rigid	230	1 1/4	4 1/4
ML045	4	Swivel	440	1 1/2	5 3/8
ML046	4	Rigid	440	1 1/2	5 3/8
ML441	4HD	Swivel	550	15/8	5 5/8
ML442	4HD	Rigid	550	15/8	5 5/8
MN264	4HD	Total locking brake	550	1 5/8	5 5/8
ML397	5	Swivel	650	1 1/2	6 1/2
ML398	5	Rigid	650	1 1/2	6 1/2
MN265	5	Total Locking Brake	650	1 1/2	6 1/2
ML399	6	Swivel	850	1 1/2	7 1/2
ML400	6	Rigid	850	1 1/2	7 1/2
MN266	6	Total Locking Brake	850	1 1/2	7 1/2
MN449	6	Butterfly Side Brake	850	1 1/2	7 1/2
ML401	8	Swivel	1000	15/8	9 1/2
ML402	8	Rigid	1000	15/8	9 1/2
MN267	8	Total Locking Brake	1000	15/8	9 1/2
MN450	8	Butterfly Side Brake	1000	15/8	9 1/2

BLUE ELASTIC RUBBER CASTERS

- · High load capacity, rolls easily and quietly on all floors
- Non-marking, excellent floor protection
- Zinc-chromed plated finish provides corrosion resistance
- Elastic rubber tread rejects floor debris
- Sealed double ball raceway
- Tread guards
- Ball bearing
- Brake type: Total locking

Applications:

General duty applications in mobile warehouse equipment and factory use.





Model No.	Wheel Dia."	Caster Type	Capacity lbs.	Tread Width"	Overall Height"
ML333	4	Swivel	350	13/8	5
ML334	4	Rigid	350	13/8	5
ML342	4	Swivel w/Brake	350	13/8	5
ML337	5	Swivel	400	13/8	6
ML338	5	Rigid	400	1 3/8	6
ML345	5	Swivel w/Brake	400	13/8	6

MOLD-ON RUBBER CASTERS

- · Molded rubber wheel permanently bonded to spoked cast iron core
- Iron centre gives it strength while the molded rubber offers smooth and quiet operation
- Protects loads and surfaces
- Won't damage warehouse or factory floors
- Brake type: Total locking

Surface Applications:

Concrete, brick, carpet, steel, tile, asphalt, wood and linoleum

Plate dimensions: 4" x 4 1/2" Bolt hole centres: 2 7/8" x 3 1/3" **Bolt hole dimension:** 7/16"





Swivel Model No.	Rigid Model No.	Total Locking Brake Model No.	Butterfly Side Brake Model No.	Wheel Dia."	Capacity lbs.	Tread Width"
ML846	ML847			5	400	2
ML849	ML850	ML851	MN451	6	500	2
ML852	ML853	ML854	MN452	8	600	2

HI-TEMP NYLON CASTERS

- Smooth rolling, non-marking
- Zinc chrome plated finish provides corrosion resistance
- Superior resistance to most oils, chemicals, and grease
- Double ball raceway
- Ball bearing
- Total lock brake
- Maximum temperature 230°C

Surface Applications:

Concrete, brick, carpet and steel



Plate dimensions: 4" x 4 1/2" 3" x 3 1/3" **Bolt hole centres: Bolt hole dimension:** 7/16"

100	200	2000	65V 16
100	m 111	100	DOM:
	-	March Av	00°/80
		UE I	

Model	Wheel		Capacity	Thread	Overall	
No.	Dia."	Style	lbs.	Width"	Height"	
ML861	6	Swivel	800	1 3/4	7 5/8	
ML862	6	Rigid	800	1 3/4	7 5/8	
ML863	6	Total Locking Brake	800	1 3/4	7 5/8	
MN453	6	Butterfly Side Brake	800	1 3/4	7 5/8	
ML864	8	Swivel	850	1 3/4	9 1/2	
ML865	8	Rigid	850	1 3/4	9 1/2	
ML866	8	Total Locking Brake	850	1 3/4	9 1/2	
MN454	8	Butterfly Side Brake	850	1 3/4	9 1/2	

ML017

MN226

MN225

NYLON SANDWICH CASTERS

- · Non-marking white nylon elastic rubber cushion ring layer reduces noise and vibration
- · Chrome zinc-finish for corrosion resistance
- · Double raceway
- · Ball bearing
- Brake type: Total locking

Surface Applications:

Concrete, brick, carpet and steel



KI ETROM

Plate dimensions: 3 1/3" x 4 1/8" 3 1/8" x 2 1/3" **Bolt hole centres: Bolt hole dimension:** 5/16"

				M/Na	A SACTA II SEPARATE
Model No.	Wheel Dia."	Caster Type	Capacity lbs.	Tread Width"	Overall Height"
MN441	4	Swivel	440	13/8	5 1/8
MN442	4	Rigid	440	13/8	5 1/8
MN443	4	Swivel w/Brake	440	13/8	5 1/8
MN444	5	Swivel	440	13/8	6 1/8
MN445	5	Rigid	440	13/8	6 1/8
MN446	5	Swivel w/Brake	440	1 3/8	6 1/8

PNEUMATIC CASTERS

- · Four ply pneumatic casters offer smooth and quiet rolling over the roughest surfaces and outdoor terrain
- · Shock absorbing properties give the greatest possible protection to both the load and floor
- The "Air cushion" feature will transport the most fragile material and instruments without damage
- Not recommended for floors with metal shavings or corrosive chemicals

Surface Applications:

Concrete, brick, carpet, steel, tile, asphalt, wood and linoleum

Plate dimensions: 4" x 4 1/2' 2 3/4" x 3 3/8" **Bolt hole centres: Bolt hole dimension:** 13/32"



MN221

Model No.	Wheel Dia."	Caster Type	Capacity lbs.	Tread Width"	Overall Height"
MN222	8	Swivel	350	2	10
MN221	8	Rigid	350	2	10
MN224	10	Swivel	400	3	12
MN223	10	Rigid	400	3	12

For optimum use pneumatic wheels must be properly inflated

ENVIROTHANETM WHEELS

- · Solid non-marking polyurethane used for high load capacities
- · Harder than soft rubber and softer than hard rubber
- · Top quality wheel that will not damage your floors and will not develop flat spots under standing loads
- Government approved
- Temperature: -43°C to 110°C
- Durometer: 45 65 D Scale

- Platform trucks
- Food service equipment
- Hotel equipment
- Small waste bins
- Large stock trucks
- Factory use
- Textile carts
- Abusive applications



Model No.	Wheel Dia."	Bearing Type	Cap. Ibs.	Tread Width"	Hub Length"	Bearing Bore"	
MG534	3	Nylon/Steel	100	7/8	1	5/16	Т
MG535	3	Nylon	150	1	1 3/8	5/16	
MG536	3	Nylon	250	1 1/4	1 5/8	5/16	
MG537	4	Nylon	150	1	1 3/8	5/16	
MG538	4	Nylon	250	1 1/4	1 5/8	5/16	
MG539	4	Plain	500	1 1/2	13/4	3/8	
MG540	4	Roller	650	2	2 3/16	1/2	

THERMOPLASTIC CASTERS

- · Heavy-duty double swivel raceway
- Grey thermoplastic rubber is non-marking and includes synthetic tread guards to protect roller bearings
- Durable zinc-plated pressed steel assembly for durability



Plate dimensions: 3 1/2" x 2 1/2" 2 3/4" x 1 3/4" centre-to-centre **Bolt hole centres:**

5/16" **Bolt hole dimension:**

Model No.	Wheel Dia."	Caster Type	Capacity lbs.	Tread Width"	Overall Height"	Bearing Type
ML014	3 1/8	Swivel	130	1 1/4	4 1/4	Ball
ML020	3 1/8	Rigid	130	1 1/4	4 1/4	Ball
ML017	3 1/8	Swivel w/Brake	130	1 1/4	4 1/4	Ball
ML015	4	Swivel	200	1 1/8	5 1/4	Ball
ML021	4	Rigid	200	1 1/8	5 1/4	Ball
ML018	4	Swivel w/Brake	200	1 1/8	5 1/4	Ball
ML016	5	Swivel	220	1 1/8	6 1/4	Ball
ML022	5	Rigid	220	1 1/8	6 1/4	Ball
ML019	5	Swivel w/Brake	220	1 1/8	6 1/4	Ball

FLAT-FREE CASTERS

- · Solid polyurethane wheel never runs flat
- Same bounce feel and weight of a pneumatic caster
- Smooth and quiet rolling over rough terrain and surfaces
- Less costly than traditional foam-filled tires
- Ball bearing

Surface Applications:

Concrete, brick, carpet, steel, tile, asphalt, wood and linoleum

Plate dimensions: 4" x 4 1/2" 2 3/4" x 3 3/8 **Bolt hole centres:** 13/32' **Bolt hole dimension:**



Model No.	Wheel Dia."	Caster Type	Capacity lbs.	Tread Width"	Overall Height"
MN226	8	Swivel	275	2	10
MN225	8	Rigid	275	2	10
MN228	10	Swivel	300	3	12
MN227	10	Riaid	300	3	12

WHEELS







	Model No.	Wheel Dia."	Bearing Type	Cap. Ibs.	Tread Width"	Bearing Bore"	Wheel Type
A.	MC298	5	Roller	1500	2	3/4	Cast Iron
В.	MH296	6	Roller	400	1 1/2	3/4	Rubber
B.	MH297	8	Roller	595	2	3/4	Rubber
В.	MH298	10	Roller	400	2	3/4	Rubber
С.	MC337	8	Roller	1000	2	3/4	Phenolic
C.	MC340	12	Roller	3000	2 1/2	1	Phenolic
D.	ML069	10	Ball	350	3 1/2	3/4	Pneumatic